

Building Services Engineering

Volume 19 | Issue 6 Article 1

6-1-1980

H & V News

Follow this and additional works at: https://arrow.tudublin.ie/bsn

Part of the Civil Engineering Commons, Construction Engineering Commons, and the Construction Engineering and Management Commons

Recommended Citation

(1980) "H & V News," Building Services Engineering: Vol. 19: Iss. 6, Article 1.

doi:10.21427/D7DQ4P

Available at: https://arrow.tudublin.ie/bsn/vol19/iss6/1

This Article is brought to you for free and open access by the Journals at ARROW@TU Dublin. It has been accepted for inclusion in Building Services Engineering by an authorized editor of ARROW@TU Dublin. For more information, please contact arrow.admin@tudublin.ie, aisling.coyne@tudublin.ie, gerard.connolly@tudublin.ie, vera.kilshaw@tudublin.ie.


GRILLES LOUVRES
 AND DUCTING

HEAT PUMPS - IRISH STYLE IRELAND'S BUILDING SERVICES MAGAZINE

HAW SEWS

JUNE 1980

INDUSTRIAL AND
COMMERCIAL BOILERS



FINANCE FOR SUBCONTRACTORS

WATER

...the first priority


Advantages over 'wet layup' and steel tanks are numerous . . . being hot press moulded to a high specification GRP tanks need no further maintenance, painting or descaling . . . whatever the climate!

A comprehensive range of literature describing Hydroglas tanks, their construction and assembly is available. Simply complete and return the coupon and we'll put you on our priority list.

Hydroglas water storage tanks have proved themselves throughout the World over the last decade. Wherever water storage is required, Hydroglas tanks can meet the need . . . match the priority.

Hot press moulded in corrosion resistant and

maintenance free GRP,
Hydroglas sectional water
tanks are easily and
speedily erected in even
the most difficult locations.
The lightweight Hydroglas
panels with their inherent
dimensional and material
stability are resistant to
heat and Ultra Violet
exposure.





A range of accessories are available. This ball valve chamber is one of many options available.

HYDROGLAS WATER STORAGE TANKS

Full information, please, on immensely strong, lightweight Hydroglas Sectional Water Tanks.

Name

Position

Organisation

Address

BTR
Permali
RP

BTR Permali RP Limited Jamestown Road, Inchicore, Dublin 8 Telephone (01) 265911 Telex 25764

H&V NEWS

IRELAND'S BUILDING SERVICES MAGAZINE.

Published by:



Irish Trade and Technical Publications Ltd, 5/7 Main St, Blackrock, Co. Dublin. Tel: 885001 Member of the Trade and

Professional Publishers Association

Managing Director: Gerard J Murphy Editor: Ray Loughran AMIDHE

Art Editor: John Gibney

Sales and Marketing Director: Patrick J Codyre

Advertisement Manager: Victor Gibson

Subscription Rates:

One Year £9.00; Two Years £13.50.

IN THIS ISSUE



SANBRA FYFFE OPEN DAY.



BOILERS & BURNERS......31

Show.

FINANCE AND SUBCONTRACTORS...

A New Series on Finance for the Subcontractor.

PEOPLE/LITERATURE/PIPELINE..... PAGE 15

GRILLES LOUVRES AND DUCTING..... PAGE 18

NEW PRODUCTS......PAGE 26 Satchwell New Valve; New Wavin Jointing System, Plastic Access Junction from Quality Plastics.

ZONE......PAGE 28 Heat Pumps and Energy Conservation.

INDUSTRIAL & COMMERCIAL BOIL-ERS & BURNERS..... PAGE 31

Dublin Warehouse For Armitage Shanks

Armitage Shanks (Ireland) Ltd. are expected to make early announcement regarding the establishment of a new Dublin warehouse and sales administration centre. This new warehouse is Phase 2 of their planned programme of expansion. This extensive warehouse will be a distribution centre for all Group products and from which deliveries will be made. The warehouse facilities should be particularly useful to customers from the provinces who make periodic visits to

Dublin. They will be able to collect their supplies and particularly, special application items from the tremendous range Armitage Shanks products. Identifying, and having readily available, customer requirements will be the prime objective of the new warehouse operation, states Derek Gordon, marketing manager. "We intend providing a first class, comprehensive and immediate service geared totally to customer needs."

BTU GOLF



(Left to right) BTU golfing society captain Peter Johnston with the overall winner on the day Eamonn Vickers with John Pickerill, Director of Veha Ltd.



A group of happy golfers pictured at the Veha sponsored BTU golf

https://arrow.tudublin.ie/bsn/vol19/iss6/1

DOI: 10.21427/DXDQ4Pune 1980

CIBS ANNUAL

Due to circumstance out-side of the new CIBS committee control they were unable to hold the traditional golf outing/ladies evening in May, but have been fortunate enough to be able to have this outing on Friday 22nd August in the Hermitage Golf Club, by kind permission. Members are asked to not this date in their diary now and further details will be issued nearer the date.

NEW MONSON **ADDRESS**

G W Monson & Sons Ltd have announced new additional office facilities at 8 Lower Mount Street, Dublin 2, tel: 765627, telex

£50,000 Boiler from **Danks**

Additional process steam required for plant expan-sion at Avonmore Creamery of Ballyraggat, resulted in a £50,000 boiler order for Danks of Netherton Limited. The company, one of Britain's leding boiler manufacturers, has suppli-ed an oil fired Metric Package 3-pass wet back boiler with an output of 40,000 lb/hr (11,300 KW) of steam from and at 212°F and at a pressure of 200 psig. Ordered last autumn through General Industrial and Marine Boilers Limited, agents for Danks in Ireland, the boiler has now been supplied, installed and is fully operational.

New Agency For Loughrey

Loughrey Sales Ltd., have been appointed sole Irish agents for 'Ladybird' an ex clusive range of val loaders, handstackers and industrial trucks. The Ladybird range includes three portable and genral purpose models and two models for heavy duty industrial use. The portable loaders have been designed for rapid loading and unloading. They can handle loads of up to 125 kg to a height of 1066 mm. Their great advantage says Peter Fox, manager of Loughrey Sales Ltd., is that "they can easily be operated by one man and are particularly useful where open floor space is restricted. They are completely portable and can be carried with the truck or van".

The heavy duty industria trucks can lift loads of up to 270 kg to a height of 1066 mm. The castor wheels make them very manoeuverable and they are being increasingly used for die, mould and tool handling in workshops and stores. They are also very suitable for use in hazard areas in petroleum, oil and chemical plants where power trucks are prohibited. The Ladybird loaders and trucks are all manually operated, the lift being achieved by a one-handed crank action which is smooth, efficient and fool-Maintenance proof. virtually non-existent.

Further information on the Ladybird range can be obtained from Loughrey Sales Ltd., 35 Nephin Road, Cabra, Dublin 7, (Tel: 3077222).

WALKER REPORT "OUTSTANDING PROGRESS"

An order intake of £770,000 in the month of January was the spectacular climax to another year of progress for Walker Air Conditioning. The company's business for the financial year to 31 January 1980 showed an increase of just over one million pounds on the previous year, with orders up from £2.9 million to \$4.01 million. The growth has come from increases in the traditional business areas, particularly the distribution of Carlyle air conditioning and refrigeration products in Scotland, Ireland and Northern England, as well as from two new distribution activities in the fields of refrigercomponents and ation fluids handling. Carlyle product sales increased substantially from all offices, with Glasgow accounting for 44% of the total, Dublin 44% and Belfast 12%. The growth has been particularly strong in packaged equipment and the increases have been similar in both comfort cooling and process cooling. The Fluids Hand-ling Division, supplying pumps for commercial and industrial applications throughout the Republic, successfully completed its first full year of trading. The Division is the authorised distributor throughout the 26 counties for Girdlestone Pumps Limited, whose products are used on the vast majority of Walker projects. Two additional franchises will be announced shortly to cover specialised applications outside the Girdlestone range.

In August last year Walker acquired the assets of HRP Ireland Limited, the Dublin based suppliers of refrigeration and air conditioning components. In the five months from September to January inclusive the Company's sales have increased by 30% over the same five months last year. This has been achieved by doubling the stocks and introducing more frequent deliveries to major customers as well as the opening of a Belfast branch.

"However, we see 1980 as a year of strong growth in our traditional market areas", commented Jim Anderson, Walker Managing Director. "With the market finally becoming conscious of the need for energy efficient products we are going to be better equipped, with our Carlyle franchise, to meet market needs than any other air conditioning equipment distributor in our part of the world", he added.



Italian manufacturing

come into contact with

companies interested in

complete and operating

plant for the production

of steel heating bodies

Write to Box No. HV06

company wishes to

the purchase of a

(heating radiators).



Signing the mechanical installation and piping contract for the Nippon Denkai (Ireland) Ltd. plant in Cork are (left to right) Mr. Eiichi Izumi, Director and General Manager, Nippon Denkai (Ireland) Ltd., Mr. J. R. Hawyes, Managing Director, Irish Industrial Fabricators Ltd., and Mr. Yasufumi Eto, Asst. Manager, Production, Nippon Denkai (Ireland)

DUBLIN GAS PIPELINE

The Government is considering building a pipeline from Cork to Dublin that could result in natural gas being used in Dublin homes by 1985, but only if the Alliance & Dublin Consumers Gas Company greatly improves its performance, the Tanaiste and Minister for Energy, Mr. George Colley, announced recently.

Castigating the company for its poor management record, its overmanning and labour relations, the Tanaiste said that were the company not given its recent price rise, it would have had to close down.

A condition of the rise, imposed by the Government, is that it bring in outside management experts to monitor its progress in reforming its operation. It will take between one and three years before judgement can be passed on the company, Mr. Colley said.

The question of a pipeline would not arise until

then.

Meanwhile an Bord Ghais is undertaking a feasibility study of the proposed pipeline, which would cost over £100 million. Four routes are being considered, as well as feeder lines to some of the provincial gas companies.

Asked about the ailing gas facility in Limerick, owned by the Corporation, Mr. Colley offered little hope of its survival, pointing out that were it even now to be granted a natural gas supply it would take three years to implement the decision.

Limerick Corporation is still hoping that Mr. Colley will be able to save the municipal gas company and the jobs of the 70 people employed there by diverting natural gas from Cork to Limerick, via Mallow and Charleville,

Representations are being made by the Corporation to the Minister to include Limerick in the national grid

The City Manager, Mr. T. F. McDermott, in a report to the recent meeting of the City Council, said that because of losses amounting to over £800,000 in the last two years, they would have no option but to close down the gas company by October 1st next.



The new pallatiged system for handling Clayware pipes from Dogget Engineering.

AUTOMATED CLAYWARE PIPE HANDLING

P. F. Doggett (Engineering) Limited the Slane based firm manufacturing Clayware Land Drainage Pipes, Clayware Flue Liners etc., have introduced a new palletized system of handling items products. Up to 1.5 tonnes of pipes is strapped on standard 4' x 5' wooden pallets as the ware is being unloaded from the kilns. Full pallets are then loaded by Fork Lift Truck on to delivery lorry, each lorry is equiped with a HIAB type crane which enables the lorry driver to off load a full 20 ton load at custom-

ers site or yard in under 30 minutes. The ware is left with the customer on the pallets supplied. This enables the customer to pick up full pallet loads again with his own loader to take some to the drainage or building site as the case maybe. Handling Clayware Pipes has been a major problem in the past and this new development is regarded as a major step forward by Doggett Clayware goods have be manufactured at the Slane works for over 100 years.

INTERNATIONAL BUILDING SERVICES SHOWS 1980—1982

BUILDING PRODUCTS	& SERVICES &	
GRAHAM EXPO	Olympia	15-19 June 1980
ENERGY SHOW	NEC	24-26 June 1980
SOLARTECHNIK '80	Hamburg	24-27 June 1980
HOME		
IMPROVMENTS	London	29 Sept-5 Oct 1980
ARAB BUILD '80	Bahrain	9-14 Nov 1980
IHVEX	Dublin	17-19 Feb 1981
INTERNATIONAL HEA	TING, REFRIGERA	TION AND AIR
CONDITIONING	Utrecht	16-21 March 1981
ISH	Frankfurt	17-22 March 1981
INTERPLUMB		
HEATEX	London	Spring 1981
ENERGY 81	Essen	19-22 May 1981
HEVAC/EXPOCLIMA	Birmingham	Spring 1982

Babcock
-Bristol
Appoints
Irish
Sales
Agent

Babcock-Bristol Limited — a member of the Babcock Industrial & Electrical Products group — has appointed Measurement, Control & Automation Limited as sole agents to represent the company's Power & Water and Process Industries divisions in the Republic.

IIRS New Meat Fridge Plant

A special refrigeration installation, for use in research into meat processing, has recently been completed by Cross Refrigeration Limited at the I.I.R.S.'s new extension at Ballymun Glasnevin. Road, installation, comprising Foster equipment, includes a blast-freezer, a low temperature room and a chill room. Its use will be extended to other forms of research in the future.

https://arrow.tudublin.ie/bsn/vol19/iss6/1

DOI: 10.21427/D7DQ4P 4 IHVN News, June 1980 et al · H & V News

Carlyle from Walker is energy efficiency

1 The unbeatable range of energy miser heat pumps






2 Heat reclaim reciprocating chillers featuring double bundle condensers

3 Multi-compressor water chillers giving lower part load running costs





Moduline and Modubox
 VAV systems with inherent
 self-balancing savings

(5) Unikal computer programme analysis to assist you in (9)



selection of the most energy efficient system



the air conditioning leader

Walker Air Conditioning A member of the Jefferson Smurfit Group

Dublin Industrial Estate, Finglas Road, Dublin 11. Tel: Dublin 300844 Telex: 4862

9a Cherryhill Road, Dundonald, Belfast BT16 0JH. Tel: Dundonald 5235 Telex: 747681

Washington Road, Unit 10B, Abbotsinch Industrial Estate, Paisley PA3 4ET Tel: Glasgow 887 0551 Telex: 779406

Also Edinburgh (Tel: Edinburgh 553 1720)

Energy Efficient Buildings Symposium

The Tanaiste and Minister for Energy Mr. George Colley TD officialy opened a two day symposium "Energy-efficient Buildings" presented by An Foras Forbartha in association with The Royal Institute of the Architects of Ireland in Jury's Hotel, Dublin. Picture shows (left to right) Mr. Bernard Tighe, Chariman of An Foras Forbartha; Mr. George Colley TD, Mr. John O'Reilly, President, Royal Institute of the Architects of Ireland and Dr. Liam Downey, Chief Executive, An Foras Forbartha.



MACAWBER APPOINTS IRISH AGENTS

One of UK's fastest growing companies, Macawber Limited of Engineering Doncaster, South Yorkappointed shire, has (Ireland) Thermplant Limited as sole distributors of its products throughout Ireland. Macawber Engine-ering is fast becoming a world leader in the field of pneumatic conveying of bulk solids and has experienced a phenomenal growth record since its foundation just six years ago. During that time Macawber has

established a sister company in the USA, a subsidiary in West Germany and a string of agents around the world.

The appointment of Thermplant (Ireland) Limited will step up the availability of Macawber's unique "Denseveyor" pneumatic conveying systems to this important industrial market. Mr John Hoey, Thermplant's Managing Director commented: "There is no doubt that the "Denseveyor" is one of the

most exciting technological breakthroughs in the field of solids handling ever seen. With the "Denseveyor" it is possible to pump a wide range of solids through standard mild steel pipework in a fully automatic, totally enclosed way. This fact alone has tremendous environmental advantages for many bulk materials."

"In addition to this, the "Denseveyor" is the only system in the world which can handle most types of

coal — making it possible for the fist time to coal fire boilers with much the same ease as oil or gas. We see a tremendous market for this product in Ireland, an already we are winning significant orders."

Under the terms of the agency agreement, Thermplant have sole distribution rights for Macawber systems in Ireland, and are available to give advice on total systems and carry out turnkey operations as required.

We are back in communication again (or were we ever?)

We are sorry you could not contact us until recently due to phone problems. We are now in business



at

Thermplant



Thermplant (Ireland) Ltd, 2 Deansgrange Industrial Estate, Kill Avenue, Co. Dublin. Tel: (01) 850222/850641 Telex: 4409

https://arrow.tudublin.ie/bsn/vol19/iss6/1

DOI: 10.21427/D7DQ4P 6 IHVN News, June 1980



Taking a serious view at the Braithwaite stand are (left to right) Bill Lindsay (John Paul Mechanical), P. Feehily (Seamus Homan & Assoc., Consulting Engineers) Derek Sirrell (Braithwaite & Co. Structural Ltd.), Des O'Reilly (John Paul Mechanical) and Tom White (Finheat Limited).



Discussing the qualities of Mathews & Yates equipment are (left to right) Gordon Taylor (Climate Engineering) Tim O'Flaherty, (Finheat Limited), Neil Pollitt (Marketing Manager, Mathews & Yates) and Mr. J. Connelly (Abbott & Partners, Consulting Engineers).



(Left to right) Talking to John Grice, Export Manager, Myson International at the Myson RCM stand are Tony Hoyne (Hoyne Heating), John Harper (MacArdle McSeeney & O'Malley, Consulting Engineers) and Brian Maguire (Finheat Limited).



Frank Treacy (I. E. Lynskey Ltd.) far left discussing the finer points of Pressurisation Units and Booster Sets at the Baric Pump Stand with R. Kilday (Baric Pumps) Lorcan W. Murphy (E.S.B. Industries Div.) and J. Sowden (Baric Pumps).

FINHEAT EXHIBITION

Finheat Ltd. recently held a very successful exhibition in Jurys Hotel, Dublin, on show were products of their principals including, Myson RCM, Mathews and Yates, Braithwaite, S & P Coil Products, Powermatic Ltd, Peglers, Diffusion Radiator

Co. Ltd., Hedin and Fenton Mechanaire.

Mr. Greg Traynor of J. N. & G. Traynor & Partners, consulting engineers, won a weekend for two in London at the exhibition.

LARGE ATTENDANCE AT IEI LECTURES

"Treatment of Water for Human Consumption" was the theme of a recent evening lecture series, organised at NIHE by the Thomond Region of the Institution of Engineers of Ireland. More than a hundred engineers,

technical personnel and students attended the lecture programme.

In the first lecture D. M. O'Hegarty, P. J. Flanagan and D. Moore, all from the Department of the Environment, reviewed both the

Irish and European legislation on the question. They also discussed the bacteriological aspects of the quality of water from rivers, lakes and underground sources and the setting of standards for drinking water.

In subsequent weeks topics such as "Preliminary Treatment Processes", "Filtration and Post-Filtration Processes" were dealt with.

B&E Boilers Reception



(Left to right) Michael Gannon, James O'Malley, Murdock Foley, Bernard Keaveney, and Derek Allen.



The Irish representatives for B&E Boilers are seen here talking to fleft to right) Fergus Redmond, Hugh Siddall (B&E Boilers Irish Representative), Harry Lawless and Pierce Tiernan (B&E Irish Representative).



Pictured at the B&E Boilers reception in the Killiney Court Hotel Dublin were (left to right) Derek Allen, B&E Boilers; Eric Kinsella, Larry Kane, Ken Tidd, B&E Boilers and Tom Condon.

KING COAL TO DUBLIN

A seven-feet thick "coal seam" was recently revealed in Dublin — but it was not to be the answer to the country's energy supply problems. For the "coal" seam is a lifelike replica in fibreglass and it was on the stage at the Royal Dublin Society — not beneath the foundations. It formed backcloth for an illustrated lecture and demonstration given by the UK's National Coal Board under the title "Power Below".

The 1979/80 Faraday Lecture, organised by the Institution of Electrical Engineers in memory of scientific pioneer Michael Faraday, told the story of the introduction of electrical power into the potentially hazardous environment of coal mines. It is the first time for several years that the lecture had been brought to Ireland and Dublin was the last port of call on a lecture tour which started last October and has involved visits to 18 major towns and cities.

The lecture came to Dublin on Wednesday, May 21st, with an afternoon presentation mainly for students and senior school-children from a wide area. The evening presentation was for members and friends of the I.E.E. and tickets were available for

the general public

The audiences saw in demonstration, films and photographs some of the complex equipment which had been designed in recent years to make the coalminer's job safer and more efficient. In one demonstration a team of young NCB engineers built on stage a full-size replica of a giant coal-cutting machine, while in another a coal mine computer control desk is wheeled on stage and operated by a member of the team. The title of the 51st Faraday Lecture, had two meanings. It referred first to the vast reserved of power below the earth of this country, locked away in our rich coal seams. But it referred also to the technical problems involved in taking power beloground; taking electricity into the potentially hazardous environment of a coalmine as a source of mechanical power and of light to enable that power source to be exploited. With photographs and films of mining installations and practical demonstrations on stage of some of the complex equipment involved, the lecture gave a fascinating glimpse of a little known world. Local organisation was by the IEE and Coal Information Services.

NEW ADDRESS

Thermoplant (Ireland) Ltd are now at: No. 2 Deansgrange Industrial Estate, Kill Avenue, Deansgrange, Co. Dublin, tel: 850222/850641.



(Left to right) Gerry Curran of Temperature Controls Ltd. the sponsors of the CIBS Students Award, Michael McDonagh the new chairman IBS, and Sean Mulcahy the adjudicator.




The three CIBS Students Award winners (left to right) Derek Brown, Paul Cantwell, Derek Waters.

CIBS ANNUAL STUDENT AWARD

10 papers were submitted by students, all from the College of Technology, Bolton Street, for the Annual Student Award. The papers were adjudicated by Sean Mulcahy, who had nominated the three award winners. These were, Derek Waters, who produced a paper on glass, Paul Cantwell who produced a paper on Energy Conservation in Irish Housing, and Derek Brown who wrote on cheap hot water from solar panels. These three students presented their papers to the Institute at a recent technical meeting. After the papers were read, Sean Mulcahy announced the order of winners, and Gerry Curran of Temperature

Controls Limited, who very kindly has offered to sponsor our Annual Student Award, presented the prizes. Ist Prize (£200) Paul Cantwell; 2nd Prize (£100) Derek Brown; 3rd Prize (£75) Derek Waters.



"3 Heavy Fuel Oil Storage Tanks at Manchester, Total Capacity 450,000 Gallons"

BORSARI & CO

CH-8702 ZOLLIKON-ZURICH SWITZERLAND

Telephone: 010 411 65 86 55

Established 1873

FUEL OIL STORAGE TANKS

OF REINFORCED CONCRETE TILE-LINED IDEAL FOR ALL GRADES OF OIL

COLD WATER STORAGE TANKS

OF REINFORCED CONCRETE WITH SPECIAL LININGS

Built underground or in basements in any shape, size or capacity

IN FACTORIES, SCHOOLS, UNIVERSITIES, HOSPITALS, OFFICE BLOCKS, PUBLIC BUILDINGS, HOUSING SCHEMES (DISTRICT HEATING)

NO CORROSION-NO MAINTENANCE

Successfully in use since 1900

Erection on site — quick service
Many British and Continental references
Estimates and Representative's visit free
of charge



Sanbra Fyffe Limited, recently played host to over 700 guests at the company's Open Day. Pictured at the Open Day were; (left to right) Mr. Frank Webb, Managing Director, Davis King & Co. Ltd.; Mr. Brendan Byrne, Sales Director, Sanbra Fyffe Ltd.; and Messrs. P. King, Director and Padraig King of Davis King & Co. Ltd.



Also pictured at the Open Day were: (left to right) Mr. Ted O'Connor, Pulvertaft Ltd., Cork; Mr. Frank Quill, Ward & Goldstone, Cork; Mr. John Darcy, Managing Director, Sanbra Fyffe and Mr. Gerry Byrne, Heiton McFerran, Howth.

Sanbra Fyffe Open Day

Sanbra Fyffe Limited, which is owned by the Delta Metal Company and the TMG Group Limited, have announced at a recent 'Open Day' details of their recent capital investment programme. The company has invested £1 million over the last three years in plant and machinery, and a further investment of £250,000 is planned for 1980. The factory premises have been expanded by 8,000 sq. feet. Among the

additional items of plant and machinery are some sophisticated stamping presses, chucking automatics and automatic polishing equipment, "Re-investment in the plant has always been a policy in Sanbra Fyffe", Mr. John Darcy, Managing Director said recently at the company's Open Day. "Our production processes, consisting of hot brass stamping, sand and gravity die casting, machining, assembling, polishing and

plating, have been highly developed. Automation has been introduced into many areas, making the Sanbra Fyffe plant as efficient and up to date as any of our overseas competitors", he added. The investment has enabled the company to increase production which has been running at record levels in recent months, and thus the service to the merchant trade has been greatly improved. capital programme will con-

tinue and this year we plan a further investment of £250,000 in our plant", Mr. Darcy said. Sanbra Fyffe manufacturers an extensive range of almost 300 different Instantor fittings as well as a wide variety of plumbers brassware including the Saflo and Irlin ranges taps and mixer fittings. Its product are sold through leading builders providers. There are 300 people employed at the factory in Santry.

Walker Training Session

The lecture room in Walker's offices on the Dublin Industrial Estate was put to good use recently when a three day course was held for their Service Engineers. The course is part of an intensive training programme by Walker Air Conditioning, to maintain the highest standards of technical expertise among service personnel. Lectures purchased Carlyle's https://arrow.tudublin.ie/hsp/19/issocilies centrifugal plant.

Carlyle's European service back up team, explaining the recent developments in Carlyle's centrirefrigeration machinery. In keeping with Walker's after sales service policy the company plans to hold a customer/operators course in Ireland for interested personnel from companies which have Carlyle's



The photograph shows: A group of Walker service engineers who attended the 3 day course at Walker Air Conditioning Ltd.'s offices in

DOI: 10.21427/D7DO4P



Pictured at the recent Parkray training course were (left to right) Eric Phite, Instaheat Ltd agents for Parkray; Bob Smith, Ray Byrne and Martin Darby.



the Parkray technicians giving instruction on the installation of an inset room heater.

Change of Name for Vent-Axia Distributors

Armstrong Autoparts (Ireland) Ltd, are now part of the GKN Group of Companies, will trade under its new name, as and from April 26th, 1980, as follows:-

GKN Autoparts (Ireland)

Ltd.
Camac Close,
Emmet Rd,
Inchicore,
Dublin 8.
Tel: 01-781700.

All the services, and stocks offered by Armstrongs, will be maintained, and further developed by GKN Autoparts (Ireland) Ltd. There will be no change in address, telephone, or telex numbers. The latest Vent-Axia Manual is now available, and copies can be obtained by contacting:- M. F. Randall, Sales & Marketing Manager.

IIF GET PIPING CONTRACT

Nippon Denkai (Ireland) Ltd. has awarded £100,000 contract for the of mechanical equipment and piping at their new Cork plant to Irish Industrial Fabricators Ltd., Kinsale Road, Cork. The contract involves the installation of process equipment and site fabrication and erection of u. P.V.C. piping. The form of piping specified has not been extensively used in Irish construction up to now, and at the request of Nippon Dankai, I.I.F. has initiated a training scheme to qualify selected welders in the specialised techniques required to meet the exacting international standards. Mr. Eiichi Izumi, Director and General Manager of Nippon Denkai (Ireland) Ltd. stated that he is satisfied that I.I.F. will meet the

standards that have been set. Irish Industrial Fabricators, which was formed in 1963, undertakes quality welding and mechanical engineering projects, steel-work fabrication and erection, and workshop fabrication to recognised international engineering standards. Since 1978, the company has been part of the Sisk Group of Companies. It presently employs 200 operatives and tradesmen in various disciplines. Nippon Denkai, a Japanese company, is one of the world's leading producers of electrolytic copper foil. The foil from the Cork plant will be for use in printed circuit boards in the computer industry. Its entire output will be exported and production will commence in October 1980.

New Auto-Ranging Digital Avometer

Avo have followed up their successful DA116 digital multimeter with an additional portable model in the same size and styling. The main feature of the new DA117 is fast auto-ranging on all ranges, including current. The measurement ranges cover ac or dc voltage up to 1000V, ac or dc current up to 2A plus 10A (manual), resistance up to 20M . Range extension accessories and eht and RF probes are available extras. There is also a semiconducter junction test of 0,5mA, reading the voltage drop 0 to 2,000V. The 3½ liquid crystal display has clear 13mm high characters and includes symbols for overrange, battery low warning, range held manually, dc polarity, a large decimal

comma and unit measurement. The auto-ranging response on all dc and resistance ranges is extermely fast, less than 1 second.

There are several interesting features in the design of the instrument. DA117 is the first Avometer to use a CMOS, large scale, custom designed, integrated circuit. This 40 pin unit, produced by GEC Semiconductors Ltd, yields the advantages of very fast auto-ranging, cost saving (50 standard ICs would be needed to do the same job), bulk reduction, and good battery life, typically 400 hours from 4 ordinary HP11 zinc/carbon cells. There are also 6 standard ICs in the circuit.

Avo products available from Industrial Instruments in Dublin and Cork.



The Brennan Groups stand also at the Energy Buffet Display.



The D W Products International stand at Energy Buffet Display.

Energy **Buffet Display**

An informal buffet display was held recently in the Gresham Hotel Dublin. The theme was Energy, H & V and Air Conditioning and a number of companies displayed energy efficient products, also present were

the I.I.R.S., An Foras For-batha and An Foras Taluntais. A seminar was also held during the display and the subject of Energy Control Developments Options was discussed.

CIBS Republic of Ireland Region Office Bearers and **Committee 1980/81**

At a recent meeting of the CIBS the following were elected: Chairman, M. Mc-Donagh; Vice Chairman, T. J. L. Kane; Secretary, M. D. Buckley; Treasurer, J. J.

Murray. Committee: D. committee.

Cooney, M. Moloney, T. Purcell, D. Byrne. Two more members have to be co-opted to complete the

NEW DISTRIBUTOR **FOR ACTAIR AIR CLEANERS**

Thompsons Air Heating and Ventilating Ltd, Short Castle, Mallow, near Cork, (Tel: Mallow 21521) are to distribute Actair electrostatic air cleaners throughout the Republic of Ireland on behalf of the manufacturers Actair International Ltd of Penarth Road, Cardiff. The Actair range of electrostatic air cleaners includes packaged units of 500 to 3800 m³/h (300 to 2200 cfm)

capacity, modular units for incorporation in ducted systems of up to 30,000 m3/h (17600 cfm) capacity and mobile models which can remove welding fumes, asbestoes dust etc at source. They operate by re-circulating the air to be cleaned through high-voltage collector cells which remove particles of pollution down to a size of only 0.03 micron.

GOLF OUTING



Enjoying the evening sunshine were this happy group of IDHE golfers.



Pictured with the winner of Class 1 were (left to right) Gerry Griffin, Bill Penrice, Chris Furlong, John Berkery, (Class 1 winner) and Donal Collins from Barlo Heating Ltd the sponsors of the outing.

The Republic of Ireland Branch of the IDHE held its first golf outing and dinner on the 16th May last at Bodenstown GC on a day of glorious sunshine. The prizes were sponsored by Barlo Heating Ltd. The following are the results of the outing:-

Prize winners were: Class 1 - First, John Berkery.

Second, Garry Stewart. Third, Eamon Cullen.

Class 2 - First, Chris Furlong. 2nd, Jim Lee. 3rd, Cyril O'Meara.

Best 1st nine, Kevin Led-wick. Best 2nd nine, Owen White. Other prize winners were, Michael Melligan, W. Madigan and Joe Hogan.

DOI: 10.21427/DZDQ4P, June 1980

BARTOL CONFERENCE



Sales staff of Bartol Plastics board an Aer Lingus Boeing 737 jet at Liverpool Airport for their annual conference, held in Dublin. Foreground: Bob Jones, Bartol North West Regional Sales Manager, with Pat Carroll, Aer Lingus District Sales Manager, Liverpool.

Congratulations Victor

Congratulations to Victor Advertisement Gibson, Manager H&V News, and his wife Anne on the birth of their daughter. Will this put an end to Victor's recent excursions to the golf course?

We recently received this notice for our classified ads:

Unused Golf Clubs for Sale A set of almost unused golf clubs for sale. Owner has no further use for them.

V.G. Could this V.G. be our Victor?

A New Journal Dealing With Renewable Energy


The publication of a new journal covering renewable energy sources and their application has been announced by The Construction Press Limited. The Coordinating Editor is Dr. Alan Sherratt, Assistant Director of Thames Polytechnic, London, who has wide experience in the field of energy conservation and a particular interest in the provision of controlled environments in buildings. The International Journal of Ambient Energy will concentrate on renewable energy sources including energy collection, its conversion to usable forms and new applications.

Direct heat from the sun, wind energy, wave energy, the role of biomass, ocean heat exchange, tides, geothermal energy,

building design, thermal storage and application of ambient energy in developing countries are all topics that will be covered by The International Journal of Ambient Energy. The Journal will contain papers describing new research, case studies of interesting and novel installations and reviews and assessments of current areas of interest. There will also be a comprehensive section detailing new books and published reports with full reviews of a selection each quarter.

The Journal is published by The Construction Press Limited, Hornby, Lancaster, England (Telephone: Hornby (0468) 21888) a subsidiary of the Longman Group from whom further details can be obtained.

ARE YOU GETTING THE MOST OUT OF YOUR FUEL?



GEORGE KENT ELECTRONIC PRODUCTS

Specialists in Flue Gas analysis



INDUSTRIAL INSTRUMENTS LTD THE INSTRUMENT PEOPLE

6 Herbert Place, Dublin 2. & Little Island, Cork.

Phone: (01) 761691 (021) 822224

Telex: 24789 IIL EI

13

FINANCE FOR SUB-CONTRACTORS

GETTING PAID

The success or failure of any growing company in the construction industry, and in particular subcontracting, depends mainly on the operation and control of its cash flow. This function within a small company is not given the priority it as most deserves, individuals having formed their business from a small capital, concentrate on completing the work, satisfying the architect, and ignoring the whole idea of it all - getting paid.

This attitude by small companies is only to be expected as the self appointed directors have a technical background and have progressed up the ladder from site training commencing with a four or five year apprentiship, a period of time as tradesman, a foreman, a supervisor and then possibly some training in the control of material and labour requirements for various contracts.

reached Having this stage of their trade they decide to begin their own business having gained valuable knowledge in how to start, control and complete a contract and with their experience this presents no problems whatsoever. However, a close look at the success rate of small contracting firms started this way reveals a small percentage of actual progress and in fact most stay at the level they originally started, showing no growth at all.

The main cause of this is the lack of finance or the lack of knowledge, or interest in controlling the financial activities of the operation. This is due to claims not being submitted on time, not being persued through the various stages and therefore payments not being received. The subcontractors money is therefore being used by others while he pays overdraft interest to banks. These charges absorb all profit,

Over the next few months we hope to illustrate some simple methods (involving the minimum of time) on the operation and control of company finance for small subcontractors.

CLAIMS: INTERIM Claims are normally submitted monthly but on small contracts or short term contracts it is advisable to issue them at shorter intervals. Where direct contracts are payment involved normally be made when due but when dealing with consultants, quantity surveyors, architects and builders, it is important to follow up each stage of your claim until the builder actually writes the cheque.

The preparation of monthly claims is also very important in ensuring payment and the example shown in Figure 1 should be used on all claims submitted. On receiving an order for a contract, obtain the name of the main contracter, the architect, the quantity surveyor and consultant. As the builder will already have been issuing monthly claims, find out what dates he has agreed for the submitting of claims and always prepare your claim at least a week before that date. It is also advisable to forward copies to the consultant, architect and quantity surveyor.

Note figure 1: (A) On each monthly claim the figures on items 2, 3, 4 can be updated, thus showing all concerned the present value to date of the contract and therefore not waiting until final account stage to claim for extras and increased costs.

On extras it is important to establish a price when this work is requested and confirm the amount with consultant/architect without delay. On increased costs, details should be submitted with each claim and kept up to date as frequently as possible.

(B) This section is the https://arving.him.ie/bsn/voi19/isswhole basis of your cash DOI: 10.21427/D7DQ4P completed on the original tender sum you should refer to your estimate, and calculate the percentage of work completed as priced, and also include for material on unfixed and also material expected on site within say four days of the interim claim.

The value of extras actually completed should be detailed and this can be calculated from the amount of extras requested. Increased labour costs and material will be the same figure as in section A.

The amount of paperwork involved in all this would appear to be excessive but if you examine it carefully and keep your records up to date the time involved should be minimal.

Having prepared and presented your interim claims in this format you have given all concerned all the facts and figures required and there is no reason whatsoever why the claims should not be certified and paid in full. Having obtained a recommendation from the consultant, you should follow up on the following stages and ensure that when the builder receives his payment certificates you are included for the full amount claimed.

Payment from the builder should follow provided you keep in touch and establish with him when in fact he expects payment from the client.

Having received payment your contract should be at least paying for itself and your profits, if any, are not being absorbed by bank overdraft interest. On a number of contracts the same control could result in your having a surplus cash situation in which to (a) increase your working capital or (b) negotiate wil suppliers on the possibility of obtaining cash settlement discounts and therefore increasing the profits of the company. In the long term, a company can only be successful and ensure continuity by making profits.

In the short term however, a company can make profit but still be forced into liquidation because of an adverse cash flow (overtraded situation). Finally, if you have received your cash on a regular basis you are unlikely to become the of a bankrupt victim builder. More next month.

The author of the above article Robert McClean, is Account al Services Manager, Rotary Group.

W	ork Done		to Date
	Fig 1-1	NTERIM CLA	IM
	Contract ———		
	A		В
	Contract Details to Da	ate	Work Done to Date
1.	Tender Sum Nett	10,000	4,000
2.	Extras	1,000	400
3.	Increased Costs		
	Material	500	500
4.	Increased Costs		
	Labour	500	500
	TOTAL NETT	12,000	5,400
	Builders Discount	600	300
	TOTAL GROSS	12,600	5,700
	V.A.T.	378	170
	TOTALS :	12,978	5,870

PIPEUNE

By T. Piece

Irate Contractor

One of our contractor friends advised us of a rather amusing incident which befell him recently. During a telephone discussion with a prospective customer, angry words developed in the conversation between the two parties, very probably as a result of fatigue on the contractors part, who had suffered a problematic morning. One word borrowed another until eventually the contracor terminated the conversation by referring to the customer as a "smart person". Approximately one hour later a letter was delivered to the contractor's office, by hand delivery service, with the customers name at the bottom of a 3 verse poem which read as follows:-

"God be with the days When the customer was

right,
Even if he called you in the middle of the night,
Even if his attitude
Was just a little tart
Even if you thought he

was unduly smart.

God be with the days
When all services were
there
To always please the client
and treat him very fair,
To sum up, Mr.
Contractor
You're a lucky man
To be able to talk up like
that — it's nice if you can.

To finish off this little note, Because too much was said,

We were both a little hasty
— wrong side of the bed?
For my part I apologise,
I'd like us to be friends
I think it's worth this little
time to try to make

amends."

Having read the poem with much amusement, and great appreciation, our contractor friend had no hesitation in telephoning his new found poet, to express his apologies, and needless to remark, all previous animosities were quickly dispensed with.

PEOPLE



Mr Tadhg Gleeson, Financial Controller of Sheffield Insulations

Mr. Tadhg Gleeson B Comm., A.C.A. has been appointed Financial Controller of Sheffield Insulations (Irl) Ltd. He was previously an audit manager with Oliver, Freaney & Co., and prior to that worked with Craig Gardner & Co.

Cross Refrigeration Limited has announced the appointment of Mr Noel May as Service Manager with special responsibility for the Dublin area. A well known figure in the refrigeration field, he was previously Service Manager with W. H. O'Gorman Limited. In

his new position, Mr May will head a service team of fourteen engineers in the Dublin region.



Ken Tidd recently appointed Managing Director B&E Boilers Ltd.


Alan Davies has been appointed Sales Manager for Monsell Mitchell. He has been involved in the Builders Providers industry for many years and has held departmental positions within the company prior to his appointment.

LITERATURE

E-PAK AIR HANDLING UNITS

A new leaflet has been issued by F. H. Biddle Limited dealing with the E-Pak range of air handling units assembled at their Ilkeston works. This comprehensive range consists of eleven models suitable for air volumes ranging from 0.62 m³/s to 20 m³/s for cooling capacities or 0.62 m³/s to 35 m³/s for heating applications. The new leaflet incorporates information relating to an optional direct gas fired heating section and the weather-Published by ARROW@TU Dublin, 1980

proofing arrangements for all models in the range. Biddle have supplied air handling units for many prestigious projects in Ireland and abroad and in addition to manufacturing the E, V, and C Pak standard ranges will also design and produce equipment to meet special requirements. Associated equipment also available from Biddle includes heat recovery systems, ductwork, noise attenuators, chillers and cooling towers.



+ULSTER NEWS+ULSTER NEWS+ULSTER NEWS

Mr. L. D. G. Collen, Chairman of Ergas Ltd. was the proudest man in Larne, recently on the occasion of the opening of their new bulk storage depot. The Portadown based Ergas (N.I.) Ltd. now one of the major suppliers of L.P.G. in Ulster have built their depot in the confines of Larne Harbour thus allowing them to ship in their supplies direct from Milford Haven. In the light of the possible closure of the piped or town gas system in Ulster, this L.P.G. plant will be a welcome asset to the provinces energy supplies. The new depot which has a capacity of 600 tons was opened by Mr. Roy Beggs, Mayor of Larne who was welcomed at the plant by Mr. Wilf McKee, General Manager of the company.

Tyrrell Tanks Ltd., the Newry based firm who specialise in the manufacture of plastic domestic cold water tanks are to extend their activities and increase their labour force.

The tanks ranging from 25 to 100 gallons are moulded on a Carousel rotational moulding machine.

At a later date Tyrell Tanks hope to announce a further range of products suitable for the plumbing and heating trade.

The revolutionary new high efficiency high output open fire know as the Jetmaster was the subject of demonstration to architects heating engineers and fuel interest at the premises of MacGillicucy & Co. Ltd. of Great Victoria Street, Belfast.

Mr. David Gibson, Managing Director of MacGillicudy and Co. Ltd. acted as host to the visitors.

The Chartered Institute of Building Services (C.I.B.S.) have moved from Cadogan Square and their new address is Delta House, 222 Balham High Road, London, SW12 9BS, phone 01-675-5211.

Hospital, Industrial and Consulting Engineers together with representatives of the Energy Division of the Department of Commerce listened with interest when Mike Harrison, Sales Manager and John O'Toole, Products Manager of the pumps division of Crane Ltd. introduced the Crane C. R. A. fully closed condensate

https://arrow.tudublin.ie/bsn/voil 9/iss6/1sate DOI: 10.21427/D7DQ4P



(Left to right) Mr. G. Wright (left) and Mike Harrison with the Belfast sales staff of Pump Services Ltd.



(From left to right) J. O'Toole (Products Manager), M. Harrison (Sales Manager) of Crane Ltd. with G. Wright, N.I. Manager of Pump Services Ltd at the introduction of the new C.B.A. condensate recovery system.



(Left to right) E. Turner (Beges & Partners), Mrs. A. Burmison (O.B.C. Ltd.), J. McClelland (McNaughton Blair Ltd) at the Thorm reception.

+ULSTER NEWS+ULSTER NEWS+ULSTER NEWS+



Thorm introduce their new Panda range of oil fired boilers at a reception in the Culloden Hotel. (Left to right) Philip Johnson, N.I. Area Manager and Ed Martin, Northern Sales Manager with the Panda girls Miss McMinn and Miss O'Neil.



At the IDHE/UDT carplant golf outing were ifrom left to right) T. Galloway, C. Brewill, 1. Morrison, R. Best.



(From left to right) V. Stephens, R. Coid, R. Jackson, W. Kelso also at the IDHE golf outing.

recovery and booster system.

The system is handled in Northern Ireland Services (N.I.) Ltd., whose General Manager Mr. G. A. Wright also attended supported by T. Ferguson, E. Martin, R. Millar and P. Walker of their sales organisation. In Southern Ireland the system is handled by P. S. Ltd. of Wallowbrook Road, Rathfarnham, Dublin and equiries should be directed to their Sales Manager J. O'Reilly.

The C.B.A. is a unique step in the development of energy saving equipment as by improving the handling and quality of condensate return it greatly reduces the amount of fuel that a boiler needs to raise steam. In addition the application of the C.B.A. unit has indicated in the paper, laundry and similar industries that a substantial increase in throughput of product resulted.

Over 3,000 units have been installed throughout the world including installations in Northern and Southern Ireland and if listening to the views of some of the Engineers present who had already installed C.B.A. units, was any indication, then the C.B.A. is indeed a welcome addition of the energy conservation scene.

The first golf outing of the N.I. section of the Institute of Domestic Heating Engineers for 1980 was held at the popular Co. Down Helen's Bay course.

Following keen competition by the 40 members and guests, the prizes wer distributed by Mr. T. Galloway and Mr. C. Brewill, Branch Manager of U.D.T. Ltd. the sponsors of the competition.

The winners were: Mr. H. Cox, Mr. D. Parkes and Mr. R. Mawhinney in that order.

The N.I. Branch of the Institute of Domestic Heating Engineers held their Annual General Meeting in the Strangford Arms Hotel Newtownards.

Following the A.G.M. the committe for 1980-1981 was announced as follows: Chairman - Philip Johnston, Vice-Chairman - W. Hunter, Hon. Sec/Treas. - B. Page, Committee: Ian Morrison, Peter Mawhinney, Bill McMichael, Charlie Turner, Bob Montgomery, Maurice Stevenson and Roy Best (ex-officio).

COMPANIES SUPPLYING GRILLES, LOUVRES & DUCTING

Company Name	Address	Tel. No.	Telex No	. Product Name
Henry R Ayton Ltd	The Cutts, Derriaghy, Dunmurry, Belfast BT179HS	618511	74618	Keith Blackman
Aire Flo Ltd	Greenhills Industrial Estate, Dublin 12	783674		Ducting
Dan Chambers Ltd	3 Echlin St., Dublin 8	720448		Netaline
Coolair Ltd	Unit C Cookstown Industrial Estate, Tallaght, Co. Dublin	511244	31689	Baber & Colman
C & F Ltd	Glenside Industrial Estate, Mill Lane, Palmerstown, Dublin 20	364917		Lennox
C & R Ltd	Baldoyle Industrial Estate, Grange Rd., Baldoyle, Dublin 13	390064		Ducting
Castlereagh SM Engineering Co Ltd	Altona Road, Lisburn	Lisburn 6211		Ducting
Climavent Ltd	29 North Brunswick St., Dublin 7	776615	31718	Bahco, Brook Air, Holdfire/Air Power

FINHEAT LIMIT

DEFLECTO*

Grilles and registers, single and double row.






NON-VISION

Sightproof grilles for relief, transfer and circulation.



Fixed core extract grilles and registers.






ADJUSTAVENT

Square and circular adjustable diffusers with volume control.





Linear diffusers with adjustable air flow rate.



STYLOVENT*

Fixed deflection square diffusers for suspended ceilings.



VARIVENT* CIRCULAR Fully adjustable circular diffusers.


RIBBON LINE Sturdy linear grilles for floor, ceiling, wall and sill mounting.







The perfect finish for every job STOCK OCK



Then for that low-budget installation, there's our 'E' range-made from satin anodised extrusions.

34 Watling Street, Dublin 8. Phone: 778109/778120 Telex: 30751

Coolheat Ltd	16 Railway St., Lisburn BT281XG	Lisburn 76228	747086	Myson, RCM
Colt International Ltd	28 Main St., Bray, Co. Wicklow	863260		Colt
also at	31 College Gardens, Belfast	667771		
Dublin Glass & Paint Co Ltd	McGloughlin Industrial Estate, Jamestown Rd., Dublin 8	366641		Greenwood Airvac, Naco
Dixon Agencies	3 Wellington Drive, Bangor, Co. Down BT204PN			Trox
Denhu Ltd	Walkinstown Ave., Dublin 12	505954		Raychem, Lindlab Spirovent
D P Engineering Ltd	5/7 Ardee Rd., Dublin 6	977531	4289	Greenwood, Airvac
Eurenco Sales Ltd	106 The Coombe, Dublin 8	755557		Sema
Europair Ltd	Europair House, 3 Ardee Rd., Rathmines, Dublin 6	975747	5754	Hart & Osoley Duro Dyne, Calor Flex

THE SPECIALISTS IN Ductwork, Canopies and Copper Work



Tru-Flow Limited
Sheet Metal Works

CHAPELIZOD INDUSTRIAL EST., DUBLIN 20. TEL: 265984 (3 LINES)

https://arrow.tudublin.ie/bsn/vol19/iss6/1


22

Environmental Supply Co Ltd	Unit 35 Connswater Industrial Estate, Belfast BT41AL	54429		Netaline
Finheat Ltd	34 Watling St., Dublin 8	778109	30751	Myson RCM
Glowtherm Ltd	Perrytown House, Whitehall Cross, Dublin 6	513887	30841	Waterloo Longford
GKN Autoparts (Ireland) Ltd	Camac Close, Emmet Rd., Inchicore, Dublin 8 & Branches	781700		Vent Axia
Heating Wholesalers Ltd	Thomastown, Kilkenny	(056) 24171	8797	Smitka
William H Leech & Son Ltd	299 Ormeau Rd., Belfast BT73GG	645339		Greenwood Airvac
W. J. Hogg & Co Ltd	46 Ballynahatty Rd., Shaw's Bridge, Belfast BT88LE	640319		Zestaflex, Moducel, Fire-Foil
Irish Central Heating & Manufacturing Co Ltd	19 Greenmount Industrial Estate, Dublin 12	756446		Ducting
Met-Fab Engineering Ltd	Commons Rd., Cork	(021) 502338		Ducting



Hart & Cooley

Grilles & Diffusers



Large Supply Available Ex Stock Dublin

FIBERGLAS INSULATION

DURO DYNE SHEET METAL ACCESSORIES

FLEXIBLE DUCTING

Europair (Ireland) Ltd

Europair House, 3 Ardree Road Rathmines, Dublin 6 Tel: (01) 975747 Telex: 5754



Centrifugal Fans 7" to 36"



McCraig Collim Ltd	6/8 Greenwood Ave., Belfast BT43JJ	656212	747091	Royair
D & D McFarlane Ltd	51/53 Ridgeway St., Belfast BT95FB	667968	74219	Waterloo Westair
C A Parsons of Ireland Ltd	Dublin Rd., Howth, Co. Dublin	322693	5503	Ducting
Redbro Ltd	Unit 12G Cherry Orchard Industrial Estate, Dublin 10	266677	30898	Trox
Sweeney Sheet Metal Ltd	96 Fairview Strant, Dublin 3	887596		Ducting
Solas Teoranta	Corke Abbey, Bray, Co Wicklow	862984		Solas
John R Taylor Ltd	Naas Rd., Dublin 12	783255	5427	Ozonair
Tradfire Ltd	108 Pearse St., Dublin 2	710208		Environmark
Tru Flow Ltd	Chapelizod Industrial Estate, Dublin 20	365984		Tru Flow
Powrmatic Ltd (R Hutton)	42 Wesley Lawns, Sandyford Rd., Dublin 14	681355	919	Powrmatic
Longford Ventilators	Dublin Rd., Longford	(043) 5026	33624	Grilles
Unimack Ltd	70 Lr. Mountown Rd., Dunlaoghaire, Co. Dublin	801964		Biddle
Ventac Ltd	Grand Canal Quay, Dublin 2	713499	5307	Koolair
Walker Air Conditioning Ltd	Dublin Industrial Estate, Dublin 11	300844	4882	Carlyle
Woodside Engineering Ltd	Grand Canal Harbour, Dublin 8	780152	N.	Verrolec Zone
Whitehouse Sheetmetal & Engineering Ltd	14 Trench Rd., Hydepark Industrial Estate, Mallusk, Newtownabbey Co. Antrim BT368UU	Glen- Gormley 41328 44153 44698	ar e	Ducting
Hall Thermotank Ireland Ltd	Hall House, Main St., Rathcoole, Co. Dublin and branches	580311	30943	Hall Thermotank

GRILLES & REGISTERS EX-STOCK



Lonford Ventilator Range

Available from Sole Irish Distributors

Glowtherm Ltd



194, Whitehall Road Terenure, Dublin 6. Phone: 513887, 516644, 516531 Telex: 30841

"If we haven't it in stock you can have it in days".

Distributor for Northern Ireland required. Contact above.



Makes Air Behave

For Engineered Air Distribution

Coolair



AIR CONDITIONNING FAIR DISTRIBUTION

25 Cookstown Estate, Tallaght, Co. Dublin. Telephone 511244/511540. Mallow Road, Cork. Telephone (021)502321

ZONE EQUIPMENT

Available Ex. Stock

Fire Dampers, Blast Gate
Dampers, Flexible Ducting,
Pluseal Mastic and dispensers,
Duct Tape, Strangle-hold
Banding, Fitch Fasteners,
A Comprehensive Range of
Volume Control Damper
Components.

From Sole Irish Agents:

Woodside Engineering Ltd.

MEZ-FLANGING SYSTEM

is also Available Ex. Stock

We also Manufacture and Install

Sheet Metal Duct Work, Louvres, Volume Control Dampers, Kitchen Canopies and general sheet metal work

For further information and advice contact.

Woodside Engineering Ltd.

Grand Canal Harbour, Dublin 8. Tel: 780152/780987

Grilles, Louvres & Ducting =

GRILLES, LOUVRES & DUCTING

The following notes are based on material submitted by the companies concerned.

Coolair

Air distribution specialists Coolair Limited of Dublin are distributors in Ireland for Barber & Colman Limited, manufacturers of the world's most extensive range of air distribution equipment.

Available from Coolair, therefore, is a wide selection of louvres, grilles, diffusers, dampers, panels, terminal boxes and integrated ceilings to suit numerous applications.

Grilles:

Among the range of Barber & Colman ceiling grilles is the revolutionary continuous line diffuser Model CUD. This grille delivers the same volume per air foot as a conventional four slot diffuser and is designed to produce one or two-way patterns.

Ideally suited for use with variable air volume systems, a major advantage of the CUD grille is that air flow can be throttled down to complete shut-off without dumping taking place, thereby avoiding uncomfortable environmental conditions.

The CUD grille, which underwent extensive laboratory testing is available in a variety of finishes including anodised aluminium and bronze with maximum widths of 76 mm. for oneway units and 121 mm for two-way units.

Coolair also have a wide range of grilles and diffusers suitable for both sidewall and ceiling applications. A recent addition to the range is a new Barber & Colman integrated ceiling system, which provides diffusers designed to integrate with various types of ceiling systems.

Louvres:

Coolair's choice of louvres comprises the Model DLF Sand Louvre and the Model DL0 Extrenal Louvre. The Sand Louvre is designed to fit into air intake openings and perform initial separation of airborne sand and dust mixtures in sandy or desert locations. Constructed from aluminium extrusions, the Sand Louvre can be made from a minimum size of 300 mm wide x 300 mm high up to a maximum in one piece of 2,400 mm x 1,200 mm.

The External Louvre, also constructed from aluminium extrusions, can be used in any exterior wall opening where a continuous flow of supply or exhaust air is required, and can also be installed in any type of wall construction or at a duct terminal.

The design combines maximum free area with excellent weatherproof characteristics to allow a minimum ingress of rain water. The DL units can also be made up in the form of a door, complete with hinges and catches, for installation in plant rooms.

https

DOI: 10.21427/D7DQ4R, June 1980

Ducting:

Included in the Coolair range of ducting equipment is the Model DRO Adjustable Balancing Damper and the Econ-o-Flow Air Conditioning Terminals.

The Model DRO is a new type of damper in the form of a conical iris. It comprises an outer collar fitted with several blades which form an adjustable cone open at each end. This allows the aperture to be annular with the duct diameter and it remains annular from the minimum to maximum opening position, so ensuring a constant profile of air stream.

The Econ-o-Flow induction terminals select the correct amount of cool primary and secondary air to satisfy space cooling requirements at the lowest cost. Constructed of coated steel, the terminals are available in eight sizes from 130 to 3,200 cfm. to provide wide zone selections.

Further information on the Coolair range of grilles, louvres and ducting equipment is available from: Coolair Limited, 25 Cookstown Industrial Estate, Tallaght, Co. Dublin. (Tel: 511244)

Finheat

Finheat Ltd, sole agents/stockists for the full ange of Myson/RCM grilles, diffusers, damper and registers, claim to be fast becoming the sales leaders in that field due mainly to the policy of the company and the quality of the product

The Myson/RCM grille is easy to identify in that it is the only argan-arc welded mitred corner constructed grille available with a silver grey stove enamel finish. This particular finish eliminates the visibility of corner joints and ensures the rigidity of its construction.

Myson also do a range of secondary duct dampers which are particularly useful for controlling air flow rates in small duct sections such as branch ducts or plenum connections. Types JOD and JRD can be used for controlling the air flow rate from terminal

boxes positioned above a ventilated ceiling. All units, except JRD, can be supplied with fusible links to give a limited amount of fire protection.

Finheat's policy always been to carry the maximum stock to suit demand and this policy has proven them right time and again which is mirrored by the response they are receiving from their customers, and on special specified contracts, they are fast gaining a name for themselves for speedy deliveries. These factors, together with the full support of Myson Group Marketing Ltd, ensure that Myson/RCM grilles will have an ever increasing demand in the future

Further information is available from Finheat Ltd., 34 Watling Street, Dublin 8. (Tel: 778120).

Europair

Hart and Cooley offer a large choice of grilles and diffusers in steel or aluminium helping the heating and ventilating engineer to solve his design problem. H&C also offer mixing and expansion boxes (with or without reheat oils, either with hot water or electric), aluminium liner grilles and slot diffusers and a complete range of adjustable and multi pattern ceiling dissusers. The H&C factory in Lokern Belgium is a very modern and adequately equipped production area with stocks to meet immediate demands.

For further information contact Europair (Ireland) Ltd.

GKN Autoparts

GKN Autoparts offer a free design service to architects, consulting engineers and specifiers for ventilation problems. They also carry a very comprehensive range of ventilation units and accessories. These accessories complete the range of products and provides even greater flexibility in solving all kinds of ventilation problems.

Accessories ex-stock in-

clude: Roof plate assemblies (for flat or pitched roofs), soaker flange sheets to suit most profiles of corrugation, ceiling housingg (for ceiling void or concealed ventilation), wall plates (fixed and removeable types), egg crate grilles, non vision door grilles and external weather louvres, PVC flexible ducting in sizes 102 mm, 178 mm, 229 mm, 254 mm, 305 mm, and 406 mm and the corresponding worm drive clips.

Adaptor kits for splitting Vent-Axia fans to accommodate a large fixing thickness between the two are also available. Four core white PVC cable is supplied in minimum lengths of 5 m.

A comprehensive ventilation manual can be obtained from Vent-Axia Division, GKN Autoparts (Ire) Ltd., Camac Close, Emmet Road, Inchicore, Dublin 8. (Tel: 781700).

Glowtherm

Longford Ventilators Ltd. is a company based in Longford town and is set up solely for the purpose of manufacturing aluminium air distribution products. The aims of the company are to produce a high quality product range at competitive prices, short delivery, thus giving an efficient service to the Heating and Ventilation/ Air Conditioning contractor. A large stock of grilles is being held by Glowtherm Ltd, thus, delivery is exstock on most sizes, and due to the close liason with Longford Ventilators, delivery on non-stock items can be as little as one week. Eyelash diffusers are also available in 1, 2, 3 and 4 way discharge patterns.

Architects will be interested to note that due to the flexibility of production, aesthetic and other architectural requirements can be catered for as non standard items, providing reasonable production quantities can be assured. For further information contact Glowtherm Ltd.

Netaline *

The Netaline range of top quality extruded aluminium

registers and grilles combine clean modern lines with efficient performance.

Single and double deflector registers, eggcrate and linear strip grilles, external louvres, circular and square ceiling diffusers, linear slot diffusers, volume control dampers — they're all available in various sizes to meet all requirements.

Further details, prices, and catalogues can be obtained from Dan Chambers Ltd., and Environmental Supply Ltd.

Smitka

The Smitka duct flanging system is proving very popular with ducting manufacturers and contractors for branches, reducers, flexible connections etc., and in recent times has been used on prestige projects all over Ireland.

The main advantages in the system are the simplicity of assembly and the fact that no welding is required. HVCA approval is given under standard DW141, 1977

Further information from: Heating Wholesalers Ltd, Thomastown, Co Kilkenny. (Tel: 056-24171).

Woodside Engineering

Woodside Engineering Ltd. are sheet metal fabricators and erectors, offering a high quality service to the mechanical services industry. Having established themselves as one of the leading sheet metal ductwork companies in Ireland, they recognise the need for a good service to the sheet metal industry. Using their experience gained over the years, they set about supplying a good quality range of accessories they knew was required by the industry. This was successfully achieved by introducing the Mez Flanging System now extensively used throughout Ireland. The Zone conditioning equipment also provides almost all the needs of a ductwork manufacturing shop and they keep a constant eye on improved products as they come on the market.


NEW PRODUCTS

NEW AHU FROM

A new air conditioning unit, which may be as small as an office filing cabinet, is being launched by Bahco Ventilation Ltd. The new unit, to be called the ABCO, will have two outstanding advantages apart from its size. Normally small ventilation units will only heat and filter the air but the ABCO can incorporate cooling humidification and heat recovery as well. "It is a very adaptable unit designed for those applications where large air volumes are not necessary and would be wasteful," said Geoff Reynolds, Operations Director of Bahco Ventilation Ltd, Banbury, Oxon. "For example, it will be the ideal choice for the board room or small canteen."

Installation is greatly simplified by the modular composition of all ABC units. Modules are easily fitted together by means of a neat and simple slide rail joint. This means that the ABCO can be assembled in a variety of shapes and adapted to fit existing restricted space without special building programmes being necessary. Modularity also means that regular servicing is made easy. Each section can be treated as a separate entity. Fan units and filters will even slide out on guide rails for easy access.

A basic combination unit is available, which consists of fan, heater and filter. This will then have added to it other modules such as mixing sections. The fan may be chosen belt driven or driven direct. As with all ABC units the ABCO can incorporate heat recovery, reducing fuel bills. Heat from the exhaust air is transferred to fresh incoming air by means of a heat exchanger. There is a choice of three forms of heat recovery: thermal wheel, run-around-coil, and plate heat exchanger. The ABCO has a cross sectional area of 720 x 420 mm (no more than the area of a small coffee table top) and delivers an air flow from 0.25 -0.7 m³/s (440 - 1230 cfm). Bahco are represented in Ireland by Climavent Ltd.



The Danfoss solenoid valve type EVRA 25.

https://arrow.tudublin.ie/bsn/yol19/iss6/1 DOI: 10.21427/D7DQ4P

Wavix, Wavin's New **Jointing** System

new addition to the Wavin comprehnsive range of fittings is the highly efficient Wafix fixed seal jointing system for the Wavin-Sewer, and soil, systems. It will be introduced on the 110mm coupler, long radius bends, and curved channels. The seal used in this system is premanently held in position with a polypropylene click-ring. Consequently, joints can be made quickly and easily. The Wafix's rubber click-ring will withstand wide fluctations in temperature and will remain fully effective under vacuum. Wavin's research and development division conducts an ongoing programme of product refinement, and the design of fittings for new applications. The Wafix system is one of a number of advances resulting from the programme. Wavin is unique in this country in that it manufacturers 96% of its fitting requirements for its pipe systems at Balbriggan, Co Dublin.

FROM **QUALITY PLASTICS**

Quality Plastics Ltd. has introduced a new multi-purpose 671/2° double access junction to its 110mm qualplast range of U.P.V. C. underground drainage pipes and fittings.

The new fitting can be used in a variety of configurations utilising standard qualplast socket plugs, including right-hand, lefthand or double branch entry, in addition to allowing access on a straight drain run.

Satchwell's New **Spring** Return Valves

Satchwell Sunvic have launched an additional range of two port spring return zone valves which set themselves apart from any other valves in the market in that they consist of two separate parts. Satchwell say that for the first time with spring return valves the valve bodies and the actuators are separated so that installers can, if they wish, plumb in the valve section first and then wire the actuator up later, at a more convenient time. The Satchwell Unival as it is called, is designed for the flow control of low pressure hot and cold water. It is particularly suitable for central heating applications where on-off regulation of heating zones required. actuator, which fits Satchwell's existing ML range of valve bodies, requires no earth wiring because of its double insulated body. It comes in five different sizes three of which have an auxiliary switch. The need for a separate relay is eliminated with the SZ 1302 due to the incorporation of a change-over switching facility. This allows independent hot water controls in systems using pumped central heating and gravity domestic hot water. The valve bodies also come in five different metic and imperial sizes and incorporate twin self-cleaning PTFE shoes which, irrespective of flow direction ensure positive shut-off in the closed position and trouble free operation. Compression fittings are included standard on metric pipe sizes.

NEW PRODUCTS

Principles of Vortex Shedding

Vortex is the name given to the natural effect that occurs when a gas or a liquid flows around a blunt non-streamlined object. he flow, unable to follow the shape on its down-stream side, separates from the surface of the object, leaving a highly turbulent wake that takes the form of a continuous series of eddies forming and being swept downstream. Each eddy or vortex first grows and then becomes detached or shed from the object hence, the name given to the phenomenon, vortex shedding.

If the vortex-generating object is correctly shaped and placed in a pipeline with the correct relative dimensions, it forms a primary flow element that enerates pulse signals over ry wide flow ranges at a frequency proportional to the volumetric flow rate approaching it. Shown is a preferred geometry used in the meter and the resulting regular flow pattern. The triangul-shaped flow element is placed in the pipeline with its base facing into the direction of flow. The approaching flow separates from the flow element, and the vortices form and are shed alternately on either side of the triangular shape. As the flow rate increases, the speed with which each vortex forms and is shed increases at the same rate. As a result, the number of vortices generated per second is directly proportional to the flow rate. Furthermore, the calibration factor (e.g., pulses per gallon or cubic

foot) is determined only by the dimensions of the flow element and the bore of the metering chamber. It does not depend on fluid gravity, viscosity, pressure or temperature; neither does it depend on whether the fluid is a gas or a liquid. Although the Vort-X-Cel can be supplied with alternative types of vortex sensor, it is the oscillating disc sensor which is suitable for steam. This is a small disc which is oscillated by the vortices at the shedding frequency. It moves within a magnetic field and the resultant change of inductance produces a signal which is fed to a Neptune Universal Signal Processor Model 4650 which can provide either digital or analogue outputs compatible with most instruments.

The Neptune Vort-X-Cel vortex-shedding flowmeter can be supplied to measure liquids, steam, gases and cryogens. It is available in sizes from 2 inches to 8 inches and operates at pressures up to 3600 psig and temperatures up to 700°F, with a minimum turndown ratio of 10:1. Calibration factor is constant regardless of temperature, pressure, density or viscosity changes. important optional feature of the Vort-X-Cel is a hot tap valve which allows maintenance to be carried out without removing the meter from the flow line.

Neptune Measurement is represented in Ireland by Bentley Instrument Co Ltd, 4A Greenville Avenue, South Circular Road, Dublin 8.



Elegant Shower Bath

A completely re-styled Sheraton 2 acrylic bath replaces Armitage Shank's highly successful Sheraton. The semi-luxury showerbath has a slip-resistant area at the waste end — the modified dimpled base making bathing and showering equally convenient. Fully re-inforced, it is made from acrylic sheet and is available in nine colours and white.

As with all Armitage Shanks acrylic baths, the metal support frame is glassfibre-bonded to the underside, forming a secure cradle with the legs screwed to the base board and floor fixing position. Built-in wall brackets attach to the frame on the long side of the bath and can be screwed

A completely re-styled in to the wall and tiled over Sheraton 2 acrylic bath replaces Armitage Shank's wall' fix.

Designed with similar generous internal proportions as its predecessor, Sheraton 2 has twin handgrips, and in addition dual soap recesses, a sloping back with angled neck rest area, and wide flat edges, so useful when bathing children.

A completely re-styled and curved front panel forms a toe recess running the length of the bath. Overall dimensions 1700 x 800 mm and an internal depth of 387 mm at the waste end make this a generously proportioned bath to suit most existing bathrooms.



Heat Pumps and Energy Conservation

C. P. Ford, Consulting Engineer and T. C. O'Connor and M. F. Kyne, University College, Galway.

Energy is always topical and never more so than now when certain sources of it (fuels) are in short supply. In any discussion of energy it is well to bear in mind that most people are usually less concerned about what is the primary source of that energy than about what the energy can do for them - keep them warm, cook their food, run their machines or transport them quickly and without effort.

The "mix" of energy sources in Ireland relies primarily on the imported fossil fuels of oil and coal, with significant contributions from native sources of turf, natural gas and hydropower. The harnessing of solar energy, directly through solar panels or voltaic cells or indirectly through wind, wave or energy crops, has yet to emerge from the experimental stage into economic exploitation. In judging the economic aspects of various forms of energy it is necessary to take a wider view than the final cost to the consumer. The development of native sources of energy, whose exploitation provides secure employment opportunities in Ireland and also makes the country more selfsufficient, is obviously preferable to increasing imports and aggravating our balance of payment problems. aspect Another which requires consideration is the efficiency with which the primary energy is converted into the form in which it is required such as motive power or space heating. The questions of the environmental pollution impacts of a source and whether it is renewable or https://arraw.fuclublin.jg//sn/yorla/iss6/1

This article will examine how the application of one form of technology - the heat pump - can make a significant contribution to the solution of Ireland's energy problems in the 1980's and beyond. It is based on research work carried out in University College, Galway in conjunction with local industry and national agencies such as the E.S.B. and the National Board of Science and Technology. After a brief look at how a heat pump can be applied to space and water heating we will consider the economic impact of its adoption in place of conventional heating systems for homes and installations in Ireland.

Heat Pump

The technology of heat pumps is not new. The theoretical basis for them was established by Lord Kelvin around the middle of the last century. Their practical application has been largely in the refrigeration industry and more recently in air conditioning units. They have not been widely used in the "heating mode" for space and water heating because this could be done more cheaply and conveniently

by conventional electric or combustion processes. However, with the present escalation in energy costs it makes sense to examine closely a method which gets more than half of its energy output "free" from the environment.

The heat pump, as its name implies, is a device like a refrigerator for pumping thermal energy from one place to another. It can extract energy from a source of low grade heat such as ground water or outside air (even at sub-zero temperatures) and transfer it, at a higher temperature, to warm up say indoor air or water in a radiator system. It required an input of energy in a conventional form such as electricity or an internal combustion engine to drive a compressor and circulating fans. The great advantage of the heat pump however is that for the expenditure of one unit of electric cal energy it can deliver two to five times this amount of equivalent energy in the form of heat depending on the application or temperature lift involved. In other words we now have the ability to pick up 50% or more of all our residental space and water heating requirements from energy available in our environment. We can use the earth's survace and the lower atmosphere as a giant collector of solar energy and thanks to the Gulf Stream and the moist south westerly air stream that often covers the country, we can 'import' a lot of Caribbean sunshine!

The efficiency of a heat pump is often expressed as its coefficient of performance (COP) which is roughly the ratio of the useful energy output to the energy expended in getting it For an air-to-water heat pump suitable for the typical Irish house an average COP over the heating season might be 2.5. For applications such as swimming pool heating, horticulture, mariculture or some industries, especially if located covenient to ground water, rivers or the sea, the COP could be substantially higher. This obviously makes electricity, especially at an off peak rate, a very competitive form of heating.

Electricity is a high grade and versatile form of energy. It can be generated from many sources - in thermal stations burning the whole range of fuels from heavy residual oil, coal, gas, turf and biomass, in hydro-stations and possibly, in the future, from wind or waves or nuclear stations. A nationwide distribution system exists which is underutilized for much of the time. It suffers from the disadvantage that it cannot be stored directly and the 30

DOI: 10.21427/D7DQ4P

ZONE

demand fluctuates considerably with the time of day. A system of using electricity efficiently for heating, which would not add a great burden to the electricity supply network during peak load periods, would offer obvious advantages for the more effective use of the network now and would give a large number of people easy access to any developments in the large scale harnessing of alternative energy sources in the future. Heat pumps offer a clean and elegant technology to tap the large renewable sources of heat energy all around us in air and water. Because of our mild moist climate we are geographically the best situated country in Europe to apply it.

vational implications: Fuel import

Whilst no definitive figures are yet available, Dr. Henry's 1976 report on Energy Usages in Ireland, the more recent Government white paper on Energy - Ireland and some current figures discussed by Messrs. Kearns and McGrath of the E.S.B. in their very timely and important paper on heat pumps recently read to the Institute of Electrical Engineers, indicate that approximately 60% of our total primary energy demand is for heating in one form or another. In 1977, this amounted to some 1.88 million tons oil equivalent for space and water heating in the domestic and commercial sectors.

The E.S.B. estimates that for 1980/
1, space heating will create 2.23
million tons of oil equivalent demand for domestic and commercial space heating. It would appear that of this approximately 1.6 million oil equivalent tons will in fact be oil imports. This of course will be a mix of residual fuels for which the E.S.B. are currently paying in the order of £100/ton and refined products which by now are probably costing £150 a ton, or more, to import.

If these figures are reasonably close to the true situation, the oil import bil for this sector at current prices may be £160 to £240 million pounds. Assuming a doubling of prices by 1985 and a usage increase of 25%, oil imports for domestic and commercial heating may well be costing us £400 to £600 million by the middle of the decade.

Fuel Utilization Efficiencies

Our table attempts to highlight the implications of successfully implementing a national energy policy on heat pump development and usuage. The left hand column shows the average percentage of the total evergy content in each fuel or source which is usefully applied as heat for space and water heating over the full year. We would expect considerable objections to the efficiencies quoted for domestic oil fired central heating (55%) and gas fired central heating (60%) as the suppliers of these fuels regularly quote 75% efficiencies to the public. This latter level of efficiency is achieved in a new appliance, when it has heated up and is running under full load. When one deducts cycling losses, the loss of heat transfer caused by combustion deposits and the electrical energy consumed to drive fans and pumps — averaged over the full year, the lower efficiencies are those which are in fact realized. We would refer those interested to three major studies carried out in the U.S. which have established the lower figures to be much closer to the true utilization experienced in domestic installations. (Gordian Associates, Cassidy Kellog & Co. and the Segeler studies).

Comparisons

Examining the table, we can begin to see why it is so important to use reliable data.

Take an average four bedroom

insulated home. We should be able to heat this house for a year with the gross total energy contained in one ton of heating oil — 265 gls. provided we could recover all that energy.

Of course, we cannot - but if we could we would have obtained the equivalent heat which 12,800 kilowatt hours (units) of electricity would give us. (437 therms). In fact, a reasonably good oil fired installation will have a seasonal conversion efficiency of 55% and in order to realize the gross heat content of one ton of oil, the householder must burn 1.82 tons (482 gls.). His bill for this would be £334 and he will have incurred an import cost of £273 for the country. Had the same householder used off-peak electricity his bill will be £366 assuming he included 10% daytime electricity. However, the E.S.B. will have to burn 3.13 tons of mix to provide the gross content of 1 ton of oil in electrical energy. The import bill will now be £230 since 2.3 tons of the mix would be oil. The consumer who opts for a heat pump with a modest conversion efficiency of 2.2:1 and using nothing but daytime electricity will pay £252 for his heating season. But look now at the import implications. The E.S.B. have only to burn 45% of the fuel needed to provide the consumer with his seasonal requirements of 12,800 kilowatt hours and the import bill has dropped to £105 or less. This consumer has a clear and on-going advantage. Not alone has he a cheaper fuel bill, he is now hooked into a dependable, multiple-fueloption system for 45% of his heating needs and the outdoor air for the other 55%. Most important of all, he is creating an import energy demand costing only 40% that of his "oil fired" neighbour. The heat pump coupled to the E.S.B. will provide us with such a system, yielding conversion efficiencies of 64% to 120% from fuel mixes which will always be cheaper than the refined oil

FUEL UTILIZATION

March 1980

* 3:1 H.P. = Heat pump which has 3kW heat output for 1kW electrical input.

** Assuming good control and maintenance.

***. of E.S.B. fuel is imported oil.

ZONE

we are now burning at conversion efficiencies ranging from 35% to 65%. Here is one good anchor for a national energy policy! Apply the above reasoning to commercial applications, schools, water heating etc. where utilization efficiencies climb to 80% or better and we can begin to see really great potential for import savings and the stabilization of our long term energy demands in this sector.

What we are talking about is the introduction of an indigenous and undiminishing source of energy supply to provide 50% or more of all our space and water heating requirements for the future. We have now the means of reducing our fuel import bill to service this sector possibly by several hundred million pounds, by the end of the next decade and this potential must surely merit our keenest attention.

Job Creation

Another aspect of the adaption of heat pumps as a heating system is the possibility of creating new job opportunities in Ireland for manufacturing and servicing them. Heat pumps are manufactured in various countries such as the U.S. and Germany but most of them are designed for different requirements and climatic conditions than Ireland. Hence there is a strong case for the development of an industry to provide heat pump systems suitable for the Irish market and for export.

Irish heat pump systems specifically deigned to cater not only for new houses and flats, but also to replace or supplement boilers in radiator systems when that necessity arises, might be expected to take over each year say 2½% of the market for space and water heating in homes, commercial buildings, industry and institutions. The investment required and the savings produced indicate

that a very substantial number of jobs would be created over the decade.

However, to create and sustain these jobs some specific and strategic decisions need to be made in the next eighteen months. We are not alone in our awakening sense of environmental energy opportunities. The move towards developing heat pumps is world wide and unless we move quickly, many of these job opportunities may be lost to us!

Research Programme

Although the advantages of the widescale adoption of heat pump technology are obvious, we must hasten with considerable caution. In the public interest and to be accepted by such bodies as the E.S.B., Irish heat pumps will have to conform to strict engineering standards and these take time to develop and demonstrate. Experience warns us not to launch a vast clutch of mechanical orphans on the counytry before their time.

A good start has already been made. Late in 1973 research on airsource heat pumps in the Department of Physics in University College, Galway. This has continued with support from industry, the ESB, the National Board for Science and Technology, the Galway County Development Team and the Commission of the European Communities. Over much the same period the ESB has been conducting its own investigation into heat pumps and has installed some in private houses and in the swimming pool of their new sports complex. Officials of the N.B.S.T. have also made theoretical studies of the impact of heat pumps on the Irish energy scene with the benefit of a national energy model developed, under the auspices of the International Energy Agency, at the computer centre in Brookhaven near New York.

The results to date are sufficiently encouraging and the potential economic benefits so promising that we now need to mount a greatly increased national R & D effort involving industry, the Universities and the appropriate semi-state bodies. The next step is to build and install several engineering prototype systems for trial and demonstration over the next heating season. The major difficulties facing the commercialization of the technology are final production costs, single phase motor starting problems and noise level control. Target costs are £1400 for 2 kW input unit and £1600 for a 3 kW unit. We are now coming within sight of these. However, it is not likely that commercial quantities of Irish mad residential heat pumps will become available for two to three years.

The application of custom designed heat pumps to energy conservation or recovery in industry is already a reality. A factory near Limerick for instance is extracting 470 kW of heat from previously discarded process cooling water to heat its warehouses, with an estimated saving of 135,000 litres of oil per year, worth £20,200 at today's price and who knows how much in years to come. Other commercial and institutional heat requirements such as swimming pools or glass houses could use heat pumps and pick up 50% to 80% of their energy needs "free" from outside air or from wells, lakes, rivers or the sea, when they are conveniently located to the point of use, with obviou economic advantages.


In these days of fuel shortages and rising prices, it seems most opportune to exploit the energy in our environment and reduce our fuel import bill. The possibility is real and within our reach — a gift from nature, our climate and reasarch. Let's grasp it.

"A factory near Limerick for instance is extracting 470 kW of heat from previously discarded process cooling water to heat its warehouses, with an estimated saving of 135,000 litres of oil per year, worth £20,2000 at today's price and who knows how much in years to come."


Companies Supplying Industrial and Commercial Boilers & Burners

Company Name	Address	Tel. No.	Telex No.	Product Name
APV Desco (Irl) Ltd.	Galvone Industrial Estate, Limerick.	(061) 45211	6923	Fulton
Henry R Ayton Ltd	The Cutts, Dunmurry Belfast BT 17 9HS also at	618511	74618	B & E Boilers
& Ballentine Watson	Broomhill Road, Pottsten (Con	517922 marial	5190	Stone Vapor
B M Heat Services	64 South Street, Newtown Ards, Co. Down	815991		DSV Boilers
Bourke & Son	7 The Parade, Donaghadee, Co. Down			Yarrow land Boilers
Castlereagh S M Engineering Co Ltd	Altona Road, Lisburn	Lisburn 6211		Castlereagh
C & F Ltd	Glenside Industrial Estate, Mill Lane, Palmerstown, Dublin 20	264917 264898		Hamworthy NKI
Clarke Chapman Ltd	42 Sundrive Road, Dublin 12	971006		Thompson Cochran
also at	16-20 Rosemary St., Belfast BT11QD	27757		
Clyde Systems Ltd	John F Kennedy Drive, Dublin 12	507844	4321	York Shipley de Dietrich Ferroli
Cool Heat Ltd	16 Railway St., Lisburn BT281XG	76228	747086 Pace G	Kayanson Binns & Speight
Potter Cowan & Co (Belfast) Ltd	114-122 Henry St., Belfast BT151GG	20277	747549 Alfred	CTC, Heatrae, Alfred Allen Maxeta

DW Products International	Office Suite No 1, Donaghmede Shopping Centre, Dublin 13	315028 316015 315006	31716	Beaumont Teknigas
also at	Kittonga Industrial Estate, Belfast Road, Newtownards	814440	747790	
Euro Engineering Co Ltd	35 Barrow St., Dublin 4	680746		Euro Fuelmaster
Euro Pumps	Cooleen, Laburnum Lawn, Cork	(021) 41388		Neca, Joannes, Maxheat
also at	21 Applewood Heights, Greystones, Co. Wicklow	876448		
Eurenco Sales Ltd	106, The Coombe, Dublin 8	755557	4147	Strebel, Biklim
James Gleeson Ltd	Caherdavin, Ennis Rd, Limerick	(061) 54455/ 51731	3287	HOVAL LOOS KYMI-KYMMENE WEISNAUPT MONARCH
General Industrial & Marine Boilers Ltd	Frankfort, Dundrum Dublin 14	989433		Danks of Neatherton
Goudie Boiler Services	129 Applewood Heights, Greystones, Co. Wicklow	875142		Midcom
— Hevac Ltd	Lomond Ave, Dublin 3 and branches	379673	587	Rio, Chapee Allen Ygnis
Heating Controls & Devices Ltd	6 Ballyoran Lane, Upper Newtownards Rd, Donald Belfast BT16OTL	5111	747536	Parkinson-Cowan, Powermaster, De Dietrich, Bradlee Powermatic
also at	Broomhill Close, Tallaght, Co. Dublin	521533		
Heating Wholesalers Ltd	Thomastown, Kilkenny	(056) 24171	8797	Pensotti Pal Kristal
Hendron Bros Ltd	Glen Tolka, 144 Richmond Rd, Dublin 3	376061		Parkinson-Cowan, Bradlee, GWB- Powermaster
IES Industrial (Ireland) Ltd	41 Dawson Street, Dublin 2	710142		Maxicon Westgarth, Clayton
also at	21 Station Rd, Belfast BT39QA	595091 56368		
J. Jamison	31 Beattie Park Central, Dunmurray, Belfast			Talisman (see also John Kelly Ltd)
I. A. Kernohan	82 Gransha Rd, Bangor Co. Down	Bangor 62841		Triton Glenwed



Coal. Meeting your energy needs today and tomorrow.



Coal as a source of energy has always been readily available. Reliable. Unaffected by fluctuations of supply and importation. Now, more than ever, coal has come into its own as an environmentally acceptable fuel, and Danks provide the means to convert it into readily useable energy. With our Metricoal wet back coal fired boilers.

We have over a century's experience of boiler making. The manufacturing capacity combined with the technical know-how to meet your particular needs.

All our boilers are designed to give years of reliable, troublefree service. Whatever your steam or hotwater needs. For more details of our wide range of boilers, write to:



Irish Agent:

General Industrial Marine Boilers Ltd., Frankfort, Dundrum Road, Dublin 14. Tel: 989 433/698/865. Telex: 30870.

John Kelly Ltd	23 Station St., Belfast BT39DN	57481	74644	Talisman
K B Combustion Ltd	Wharton Hall, Harolds Cross, Dublin 6	972168		Dunphy
W H Leech & Son Ltd	299 Ormeau Rd., Belfast BT73GG	64533		Allen Ygnis, Heat Transfer
J S Lister Ltd	Adelaide Industrial Estate27983 Balmoral, Belfast BT11QD		747068	Chappee
Luke Martin & Co Ltd	1 Sandyhill Park, Drumbeg, Belfast	612141		Danks of Netherton
McCraig Collim Ltd	6-8 Greenwod Ave., Belfast BT43JJ	656212		Hartley & Sugden
MCW Ltd	10 Wynnfield Rd., Dublin 6	976729		Hartley & Sugden
P & D Macfarlane Ltd	51/53 Ridgeway St., Belfast BT95FB	667968	74219	Hoval, Fulton Tasso
P. J. Mathews Ltd	134 Lr. Baggot St., Dub 2	789055	4438	Stelrad



et al.: H & V News

BURNAWAY

G W Monsons & Sons Ltd 16 Ballyblack Road, Newtownards 812350

Cradley

Passat Heating & Marketing Ltd

31 Anne St., Ballycastle, Co. Antrim

Passat

Pillinger of IReland

20 Sycamore St., Dublin 2777007

Pillinger

Powermatic (R. Hutton)

42 Wesley Lawns, Sandyford. 681355 Rd., Dublin 14

Powrmatic

Precision Heating Ltd

Church Rd, Santry, Dublin 9

374300

Geminox, Bentone, Tasso, Amanda

Quadrant Engineers

Green St. East, Dublin 2 771411

5283

Buderus, Riello

Reconair Ltd

Unit 4A, Coolock Industrial 470611 Estate, Dublin 5 THE REAL PROPERTY.

0611 31356

Sevesco

S L Combustion Services Ltd

also at


Laherdane, Ballyvolane, Cork

51411

Robey

158 Castlereagh Rd., Belfast BT55FT 59282 59282 Robey, Wanson

QUADRANT ENGINEERS LTD



Buderus

- * Domestic and Industrial Cast Iron Sectional Boilers.
- * Ranging from
- * 60,000 Btu/h to 6.8 million Btu/h
- * Models Available for
- * Natural Draught
- * Pressurised Firing
- * and Dual Fuel operation.

Other Quadrant Products


- * Buderus Calorifiers and Radiators
- * Riello Burners
- * Happel Convectors

- * Euroflex Flexible Connections
- * Wing and Andrews Heating Equipment
- * Triple-E Fuel Additives

For Details Contact us at:

Green St, East, Dublin 2. Tel: 771411/2. Telex: 5283

E H Siddall & 174 Ballinclea Heights, 852412 B & E Boilers Pierce Tiernan Killiney, Co. Dublin 860367 H Saacke Ltd 10 Old Court Rd., Bray, 863687 Saacke Co. Wicklow Evrotherm 1A Warren Gardens, Sermet (NI) Ltd 79233 Beeston, Lisburn BT281EA Agaheat Rock House, Balldonnell, 514686 also at 4717 Sermet (Dublin) Ltd Co. Dublin **Taney Distributors** Unit 4A Avon Beg Industrial 508120 Chaffoteaux Ltd Estate, Dublin 12 Therm Plant No. 2 Deansgrange Industrial 850222 Greens, Witermo (Irl) Ltd Estate, Kill Ave., Dublin 850641 Vosperthornycroft Naas Rd., Dublin 12 John R Taylor Ltd 783255 Potterton & Branches Danstoker Unimack Ltd 70 Lr. Mountown Rd., 801964/ Beeston Dunlaoghaire, Co. Dublin 5/6 Michael Vaughan Mill St., Trim, (046)**Passat** Co. Meath 31167



Tel.: 989921, Telex 30870

https://arrow.tuduolin.ie/bsn/yol19/issf@fort, Dundrum Road, Dublin 14

36

et al.: H & V News

Weld-Moore Distributors Ltd

T Wright

Wiltot Engineering Services Ltd 1 Smithfield, Dublin 7 725432


Warmflow

73 Main Street, Maillisle, Co. Down Ideal-Standard

Leadhill House, Lead Hill, 59175 Castlereagh, Belfast BT69RU 747846

Saacke

Index compiled from information received from companies and additional information from suppliers would be welcome.




A large steam boiler under test.

RENICK ENGINEERING CO. LTD.

MARINE AND INDUSTRIAL BOILER REPAIR SPECIALISTS

BOILERMAKING WELDING SPECIALISTS

- Re-tubing
- Free Standing Steel Chimneys
- Tanks
- Ducting
- Pressure Vessels



ENGINEERING

- Complete Boiler installations
- Boiler maintenance & Overhauls
- Pump & Valve Repairs
- General Machining

ALL GENERAL STEEL FABRICATION . GENERAL ENGINEERING

STOCKISTS OF BOILER TUBES . AGENTS FOR 'SOOTVAC' MACHINE'S

BOILERS NEW AND OLD - BOUGHT AND SOLD

Call us at

Telephones: 989433 989865 989698

Frankfort, Dundrum Road, Dundrum, Dublin 14

Modern Boiler Design


The choice and selection of a boiler and its associates design is an important step and if thoroughly considered should provide long and trouble-free operation with low maintenance cost. Regrettably the selection of boiler plant is often chosen on the basis of "cheapest tender" and whilst this may prove a cheaper solution to initial capital outlay, this saving can easily be eroded in the first few months of operation due to high running cost and possible failures. Such boilers are normally highly rated and result in higher operating and maintenance costs which remain with the life of the boiler. With this in mind, a specification can be formulated, laying down sensible guidlines for certain part of the boiler. Such specification will eliminate "tight design" and whilst this will result in the initial capital cost being higher, the lower running costs and much reduced maintenance cost will provide a package selected on long term viability.

FURNACE

Inevitably boiler design starts in the furnace area. The size of the furnace tube in terms of diameter and length should be a careful "marriage" with the firing device to be offered and fuels fired. It has been the trend in recent years to place the responsibility for combustion squarely on the burner manufacturer's shoulders. However, "opting out" cannot

relieve the boiler manufacturer of his responsibilities towards such leglislation as the "Clean Air Act" and "Stack Solids Control". Such "opting out" can result in bad or total mis-matching with calamitous results on site. With the higher grades of fuel oils now on the market with marked changes in asphalting levels, more critical is the correct sizing of furnace to ensure complete combustion within the furnace tube proper.

Similarly, Natural Gas brings it own problem. Lacking in luminosity, the combustion cycle is much longer and as a result a longer furnace is desirable. To provide optimum flexibility one should combine these differing combustion techniques particularly where dual firing capability is a requirement. It is essential that a furnace design should accommodate the ability to be fired on both fuels without the need to de-rate the boiler output, particularly when firing Natural Gas. Due to this lack of luminosity when firing Natural Gas, higher furnace exhaust temperature will result and with those furnaces where little or no consideration has been given to this form of firing, damage can result, particularly at the first pass tube plate entry. It is in the furnace area that one should first seek to lay down specification requirements to avoid operating temperatures and critical burner settings. Furnace design can be expressed in terms of "furnace combustion intensity" or "furnace wall loading". The relationship of diameter to length of the furnace is equally important. However, one should combine these relationships for it would be possible



158 Castlereagh Rd., Belfast BT5 5FT. Tel: Belfast 59282.

S.L. Combustion Services Ltd.,

M. J. Morris & Co. Ltd.

Furnace Builders
Boiler Repair Specialists
Oven Builders
Industrial Furnace Erectors
Suppliers of Refractories
and Allied Products



Agents for Incinerators
Stockists and Erectors to the Clarke
Chapman John Tompson Boiler Group

For information contact:-

M. J. Morris & Co. Ltd.

Wharton Hall, Harolds Cross, Dublin 6. Tel: 972168, 972980, 972584. After Hours: 980464. or 045-64384.

//arrow.tudublin.ie/bsn/vol19/iss6/1



Heating & Ventilating/Air Conditioning/Fuel Conservation/Environmental Engineering/ Pollution Control/Refrigeration/Sanitaryware/Plumbing Equipment

Since the first lhVex in the early 70's there has never been a more appropriate time than now for an exhibition serving the Building Services Industry as Ihvex so comprehensively does.

Dramatic changes have occurred in the type of fuel being used for generating heat and electricity. With an increasingly realistic view being taken of the life of oil supply, manufacturers of heating, air conditioning, refrigeration and allied equipment have concentrated on energy conservation methods and solid fuel burning appliances.

IhVex '81 offers the first opportunity for the industry in Ireland to look at and discuss the many new types of equipment and systems that will be necessary for its survival in the future within the context of a major exhibition.

Many questions are being asked of the future - has fluidised bed combustion been fully developed? Has the heat pump a future in Ireland? Will the change over to solid fuel in domestic heating cause massive air pollution?

These and the many other questions raised can only be answered by the manufacturers and IhVex offers a perfect setting to put the facts to the entire Building Services Industry.

enue

Simmonscourt Exhibition Complex. Royal Dublin Society, Ballsbridge, Dublin 4.

Tuesday February 17. Wednesday February 18, &Thursday February 19,1981

For full exhibition details contact:



Irish Trade & Technical Exhibitions Ltd. 5/7 Main Street, Blackrock, Published by ARROW@TU Dublin, 1980 Dublin, Ireland. Telephone: (01) 885001

to have an acceptable L/D ratio but retain a very high and unacceptable combustion intensity. For conventional treble pass boilers a combustion intensity within the furnace tube proper should be limited to 41.03-51.289 Kw (140.000-175,000 Btu/cu. ft) with a L/D ration of 3.5:1 - 4:1. In selecting such design parameters, the furnace exhausts and first pass tube inlet temperature will be lower. Burner settings become less critical, albeit for optimum combustion even on conservatively rated boilers such settings should be maintained adequately.

CONVECTIVE PASSES

These are normally formed by banks of steel smoke tubes having thin wall sections. It is in these passes where further attention to design can result in improved boiler operation, higher efficiency and reduced running costs. Many boiler designs employ small diameter smoke tubes. This reduces the total convective heating surface and results in higher exhaust temperatures and pressure losses. It is common to find that with these types of boilers, efficiencies on oil are reduced to approximately 80% at

M.C.R. and, of course, still lower when firing gas.

In choosing larger diameter smoke tubes, one must be careful to assemble the number of tubes in each pass with a balanced mass flow and retain adequate turbulent transfer. This can result in a significant reduction in overall gas side pressure loss. The higher the pressure loss, the larger the burner combustion fan, resulting in large H.P. motors to drive the increased torgue requirements. Limiting gas side pressure loss to the order of 50 - 100 mm (2 - 4 ins. w.g.) will enable the burner companies to use a standard fan sizing. A further benefit will be improved combustion stability over the turn down range.

SCANTLING DESIGN


In assembling the shell design, it is always preferable for the furnace to be low set and thus avoid prime heating surfaces to cause heat surge destroying the water level as is evidenced by high positioned furnaces. It is essential to adopt wide waterways; this is particularly impoartant around the furnace tube. The furnace tube will expand and contract at

different rates to that of the first pass tubes. A certain amount of flexibility is absorbed by the bowling hoops in the furnace. However, these are substantial points of support and it is far better to take the expansion through the wet back construction and tube plate zone. In doing so this flexibility must be accurately determined to avoid movement of tubes in the tube plate. Such measurement can be accurately predicted by use of complex computer techniques.

STEAM SPACE DESIGN

This is an area where large cost savings can be made as a result of "tight design". Many manufacturers take licence of the actual evaporation rather than "F & A" rating. This approach is highly suspicious and it is doubtful that peak loads can be met and certainly the quality of steam or dryness fraction would be very low. The control of total dissolved solids levels would be difficult and the level of chemical control and blow-down would be very high and corresponingly expensive. A useful guideline is to specify steam disengagement velocity. This is given normally in the vertical plane at an approximate

QUADRANT ENGINEERS LTD



RIELLO

Press N Type Outputs up to 12 million Btu/h Suitable for 200 seconds oil

Other Quadrant Products

- * Buderus Boilers and Radiators
- * Buderus Thermoglaze Calorifiers
- * Happel Convectors

- * Euroflex Flexible Connections
- * Wing and Andrews Heating Equipment
 Triple-E Fuel Additives

For Details Contact us at:

https://arrow.tuchus.st. Fast, Dublin 2. Tel: 771411/2. Telex: 5283

DOI: 10.21427/D7DQ4P

value of 0.04827-0.0508 M/Sec (9.5-10 ft/min). It is broadly stated that at 0.05589-0.0628 M/Sec (11 - 11.5 ft/min) carry-over will occur (priming). However, one cannot ignore entirely the effects of steam leaving the surface travelling horizontally before rising to the off-take area. Here again a value of 0.1778 - 0.2032 M/Sec (35-40 ft/Min) is relevant. Providing the steam space is sized to fall within both these limits, steam space sizing will result in good quality steam with acceptable and economic control of feed water.

ACCESSIBILITY

Accessibility into the water and gas side surfaces is of prime importance. Insurance companies are becoming far more exacting during vessel inspections in manufacture and on site. Where limited access is provided, maintenance is severely restricted and the useful life of the boiler could suffer. Large manholes should be provided in the shell for water side access together with hand doors for flushing out in the lower tube plate areas. Full access should be provided to the gas side by removable doors in the front and rear smoke boxes.

Again this is important for insurance inspection and for reduction of down time during cleaning periods.

ANCILLARY EQUIPMENT

We have so far discussed the broad parameters for effective boiler design. However, one should not ignore the potential savings that can be made by "good housekeeping" within the boilerhouse. Such equipment can comprise exhaust dampers, economisers and control instrumentation. The benefits of fitting this type of equipment will vary dependent on the load characteristic, operational period, quality of manning and indeed fuel fired. For instance, one would not contemplate the use of an exhaust economiser when firing high sulphur fuels. However, careful selection can result in large fuel savings with acceptable pay back periods.

FUEL

We are all aware of the current difficulties with the choice and availability of fuel. In the past decade, we have witnessed a large swing from solid fuels to oil and gas. However, there now exists a great deal of apprehension about the availability of future energy supplies together with the continuing rises in fuel prices. Many customers are considering once again solid fuels such as coal or turf. This has resulted in a rapid re-think of firing methods and updating of old existing forms such as coking and chain grate stokers. With this form of stoking furnaces are required to be much large in diameter to accommodate the stoker bed. More advanced forms of firing are evidenced by the rapid development of the fluidized bed technique which still remains in its early stages, certainly in terms of financial viability. Other types of stoker equipment are available, such as underfeed or more modern types such as fixed bed with drop feed sprinkler arrangement. These can provide advantages in financial terms over more conventional types such as chain or cooking stokers but they too are restricted to higher quality fuels. The drop tube method of firing with fixed bed requires manual de-clinkering/ashing and thus downtime is increased. New materials are now available for use in conventional chain and coking stokers thus a wided range of fuel can be accommodated.

DANFOSS

Components for Burners and Boilers

Danfoss supplies quality components for burners and boilers.

- * Full range of Oil Nozzles in angles 30°/45°/60° and 80° in variations from 0.5 u.s. gals to 32 u.s. gals.
- * Control Boxes and Photo Cells which give fully automatic control of single and three phase burner plants.
- * Oil Pumps, Transformers and Boiler Thermostats in addition form a complete range for any burner.

Sole Irish Agents


J.J. SAMPSON & SON LTD. 12a Wexford Street, Dublin 2 Phone: 752317

Pneumatic/blown coal feed and ash removal systems can be installed giving increased automation and cleanliness of operation. However, having sized a furnace for the more

conventional types of stoker or indeed designed a boiler for eventual use with fluid bed, much of the previous comment on overall boiler design remains the same and it should be the

designer's "goal" at all time to provide a complete and acceptable package encompassing these various criteria.

With energy conservation of concern to us all, B & E Boilers associate company, Burgess & Co. (Engineers) Ltd., manufacture units from the Burgess Metro-



A B&E European hot water boiler.

B & E Coalmiser

The "Coalmiser" series is available in single and twin furnace designs up to 14,600 (32,000 lb/hr) when fired by drop feed sprinkler, chain or ram type stokers. However, one of the features of the "Coalmiser" range is that it is suitable for use with a medium depth fluid bed combustor thus providing the use with maximum flexibility for the future. Larger outputs can therefore be achieved. The "Coalmiser" is also suitable for turf firing. The larger "Twin Furnace Coalmiser' incorporates an 'original' design concept in wet back design enabling one half of the boiler to be shut down avoiding stress and increasing turn down capability. Other products from B & E include a shell boiler from the B & E "Windsor" range which exemplifies the B & E tradition for quality of design and construction, giving long term trouble free operation at high efficiFlex boiler exhaust isolator range. The damper carries full patent rights and incorporates a unique sealing arrangement and safety link feature. The exhaust damper reduces fuel and electrical usage by up to 15% per annum with pay back periods normally under one year.

Further information from Hugh Siddall or Pierce Tiernan of B & E Boiler Ltd.

Beaumont

U-Fab Limited, have recently launched the new Beaumont 1-15 heating system. A relatively inexpensive system designed for large

water heating installations, the Beaumont's capital cost can normally be recovered within the first or second year of installation, while its revolutionary direct firing design allows up to 60% savings in annual water heating cost. Typical applications include hospitals, schools. office blocks, hotels and factories.

U-Fab's new space heating system is designed to avoid plant room and flue losses caused by the on/off effect of boilers at times of

modular boilers with a novel method of connecting the boilers to the heating flow and return. In order to maintain a heating operation when a new installation or emergency repairs are being carried out, U-Fab has developed a mobile Beaumont System so that work can continue in cheaper, normal working hours without customer disruption, on an inexpensive hire basis.

information Further from D. W. Products International Ltd.



low heat demand in systems incorporating mixing valves. This is achieved by the use of a compensated control heating

Beeston

The Beeston Boiler Co. (Successors) Ltd. has luanched 2 new boilers of cast-iron sectional sectional design recently. The two new boiler ranges are the Broxley (dual oil/gas) and the Bewley (atmospheric gas), both offering new standards of efficiency and ease of maintenance. The Broxely series comprises 11 units covering outputs from 190 to 644 Kw (650,000 to 2,200,000 Btu/h). The units



The Beaumont mobile hot water and heating unit.

DOI: 10.21427/D7DQ4P IHVN News, June 1980

https://ayr.ow.tudublin.ie/bsn/vol19/iss6/1

SEVESO BOILER/BURNER RANGE



S.T.U. UP TO 5 MILL BTUPH



S.T.U. UP TO 20 MILL BTUPH



S.T.U. UP TO 1.6 MILL BTUPH

Sole Irish Agents

Reconair Ltd.

Unit 4A Coolock Industrial Estate, Dublin 5 Telephone: (01) 470611 – 470209 – 470113 Telex: 31356

Published voi intrie wa Paschery, Tolio (01) 972229 Unit 804 - 547 - 345

are designed for pressure jet oil-firing, blown gas firing or dual fuel applications for central heating and indirect hot water and incorporate Dunphy burners. The series features a new concept in section design providing easy maintenance and a high efficiency of 80% based on the gross calorific value of the fuel.

The other addition to the Beeston range, the Bewley, comprises 8 units covering outputs from 44 to 147 Kw (150,000 to 500,000 Btu/h) and features new section design, pushed nipple assembly, atmospheric gas burners, improved insulation and jacket design, contributing to an operating efficiency of 78% based on the gross calorific value of the fuel.

The ever-popular Robin Hood range has positively thrived due to its reputation for reliability and flexibility, and continues to maintain a prominent position in Beeston's production schedules. The range can be supplied suitable for

gas, oil or solid fuel firing and covers outputs from 66 to 682 Kw (224,000 to 2.326,000 Btu/h).

For further information contact Ummack Ltd.

available optionally as Class 1, 11, or 111 (150/105/55 psi). The boiler is probe-controlled and Riello gas or oil burners are fitted. The Deluxe model is specially designed — having an



One of Bradlee's new deluxe package steam boilers.

Bradlee

The Bradlee boiler is a compact and efficient three-pass, return-flame, wetback boiler. It is robustly built to BS 2790 in thirteen sizes, with outputs from 240 lb/hr up to 3.500 lb/hr and

extra man-hole at 5 o'clock and slightly higher feet so that the shell can be cleaned out from the side as well as through the usual man-hole at the back of the shell. As Bradlee boilers can be built with fittings and

openings on either the righthand side or the left-hand side, this additional feature enables the boiler's very compact design to make the best use of valuable space on customers' premises. The Deluxe model also has greater access to the furnace - for inspection or cleaning — since all the inlet and outlet pipes are attached to removeable pads (of 4'' square) which are themselves bolted to the shell of the boiler. The finish and durability of the Deluxe model has been enhanced by the fitting of a stainless cover to the cladding (which is resistant to corrosion by steam) and by using black heat-resistant paint for the remaining parts, other those which comply in the colour coding with BS 1710. Other additions have been made to the trim of the boiler.

Improvemnts have been made to the Probe Chamber, using new ceramic probes, and adding a new anti-surge fitting to the base of the chamber. New fit-

MAXECON TWIN FURNACE

Sole agents for Clark, Hawthorne, Mexican and Westgarth boilers throughout Ireland

Ranges from 3000 lbs/hr to 65,000 lbs/hr. Pressures up to 450 P.S.I.




I.E.S. INDUSTRIAL (Ireland) Ltd.

Head Office:

Ian Robinson, Managing Director 21 Station Street, Belfast BT3 9DA Tel: 732133/4

Dublin Office:

https://and Antwardination Bin Rublinis 6Tel: 710147



tings include a larger pressure gauge, a flue thermometer and the addition of a second bell. The Bradlee Deluxe Package Steam boiler is made and finished to higher standards in a number of respects than the basic Bradlee range.

For further information contact Heating Controls & Devices Ltd., Hendrons

Bros. Ltd.

Chaffoteaux

Chaffoteaux Limited markets a range of gas-fired wall hung central heating boilers specially designed to cover both the domestic and industrial fields.

The Miniflame and Maxiflame with outputs of 20-28,000 Btu and 40-60,000 Btu respectively were first introduced in 1975, and now updated as Miniflame II and Maxiflame II meet the requirements of the market perfectly well, and especially the new low-energy housing schemes. Both have an elegant modern white easy-clean case



saving valuable floor space and can be tucked away in any suitable spot around the house. Both are fitted with tinned copper heat exchangers and stainless steel burners and balanced flues. The Miniflame II, also manufactured as a conventional flue model, is admirably suited to the small house or flat, and the Maxiflame II for the larger flat or house.

Chaffoteaux have also recently introduced a new boiler, the Corvec 45, to fill

the gap between the Miniflame and Maxiflame. It is available either as a conventional flue or balanced flue model and has an output of 25/35/45,000 Btu. Corvec boilers are constructed in such a way that no electrics are required to be fitted to the boiler, and an important feature of the boilers is the unique water-differenmaster-control gas valve. Until there is sufficient water flowing through the heat exchanger, gas cannot be supplied to the

main burner. The pump etc. can be located in another area such as the airing cupboard.

Because of their simplicity, lightness and easy connections, the ease of service and installation, maintenance enables the heating engineer to keep costs down. The Flexiflame 35, suitable for the larger house or office central heating uses a single heating element to provide an output of 130,000 Btu. It is a conventionally flued boiler with draught diverter suitable for connection to a 150mm (6") diameter flue, which can be used with natural draught and with fam diluted/fan assisted flue. The Corvec boilers can also be supplied for use with LPG. Chaffoteaux products are distributed by Taney Distributors Ltd., Unit 4B Avonbeg Industrial Estate, Dublin 12, (Tel: 508120).

Danks

The highly successful range of oil, gas and coal fired

Eurenco Sales Ltd.

now appointed sole agents for




BIKLIM Boilers





520,000 Btu/h to 8 million Btu/h



224,000 Btu/h to 800,000 Btu/h

PRI


Contact

FIRENCO SALES LTD

106 THE COOMBE, DUBLIN 8. Telephone: 755557. Telex: 4147

boilers designed and built by leading manufacturers, Danks of Netherton Limited, is now augmented by a range of coal fired boilers equipped with Incendo cone type burners. These burners offer an operating efficiency of up to 82% to give exceptional savings energy. Primary and secondary air supplies produce extermely efficient combustion over the whole of the fire grate. Grits, extracted by an external arrestor, are returned for refiring as a further aid to efficiency. Another important feature is a patented banking device which allows the boiler to idle for long periods in a state of readiness to return to full fire conditions without the emission of dark smoke.

Details of this new range of coal fired Incendo type boilers and of the complete range of Danks boilers for gas, oil and burning, as well as boilers for waste heat recovery, can be obtained from General Industrial and Marine Boiler Ltd.



TL23ZHL light oil burner unit, 'T' Series (for light distillate oils up to 50 secs.) from Dunphy Oil & Gas Burners Ltd.

Dunphy

Innovation has been the keynote at Dunphy Oil and Gas Burners Limited, Rochdale, Lancs., for the last two years during which period a completely new burner range has been developed. This is the "T" Series (the letter "T" repre-

senting the Company's patented Turbine design. The range covers ratings from 200,000 Btu/H (60 Kw.) to 30 million Btu/H (8,800 Kw.). Despite this wide range the Company has been able to condense the designs into only 5 basic frame sizes. In three years

the company has completely re-structured its production line to exploit the proven advantages of its unique, patented Turbine design. (Patent No. 1553767, 1979).

Fuels covered are:

- light distillate oils up to 50 secs Redwood No. 1 at 100°F.
- heavy oils up to 4,000 secs Redwood No. 1 at 100°F.
- natural gas
- dual fuel mode (natural gas/light oil)
- L.P.G.

- sludge gas

Dunphys fans are purpose-made to their own parameters; the vital task of balancing is not left to outsiders. Each fan is individually balanced, using sophiticated new plant, to a figure equal to, or better than, the smallest achievable residual unbalance permitted by I.S.O. 1940-1973 (E). The result - a marked reduction in sound levels and a machine that is vibtation-free.

The company has recently introduced System 2000

powrmatic boilers Maximum combustion efficiency from 14 available models - 60,000 to 704,000 BTU's per hour.

COMMERCIAL, INDUSTRIAL & LARGE DOMESTIC

- Compact Free Standing Sectional cast iron hot water boilers.
- Available as either oil or gas fired.
- Standard fittings include boiler limit thermostat, temperature gauge and pre-

wired control panel.

- Highly competitive price.
- Full Powermatic Backup Service

Spowrmatic from HEATING CONTROLS & DEVICES (I) LTD.

45 Broomhill Close, Tallaght, Co. Dublin. Telephone: 01 - 521533/521635

A SUBSIDIARY OF FERGUSON INDUSTRIAL HOLDINGS LTD.

DOI: 1/0.21427/D7DQ4R, June 1980

Powrmatic Heaters also available

— a new concept in the provision of an A.O.T.C. steam boiler control panel. Produced by Dunphy engineers as a design aid for Package Steam Boiler manufacturers or for steam boiler conversions, it is available in 4 options all based on the same module

- suspended from the boiler top on a universally mounted tubular wiring conduit

- attached to the boiler casing


- attached to the boilerhouse wall or built in to a main panel

- console mounted at floor level with lockable isolating cabinet (see photograph).

All options of System 2000 incorporate the stanard 'pod'. This has a facia setting out all the necessary functions to comply with A.O.T.C. requirements in 'mimic' form in colour. All control signals lights are in appropriate colours.

Maxecon — Westgarth

The Westgarth range offers reliable performance at low



first cost. It ensures good overall efficiency at a standard pressure of 150 P.S.I.G. Designed as a three pass fully wet back single furnace boiler for use with oil and gaseous fuels. Its design criteria have been

proved and optimised by fully instrumented tests using light and heavy oils together with natural gas. Combined gas/oil burners can be supplied as required. The furnace is provided with convolutions to cater

for relative exansion. Conservative combustion intensities are used to meet current anti-pollution regulations. Satisfactory performance has been obtained without the use of small diameter tubes, with

REFRACTORIES of Bailieborough



THE FIREBRICK SPECIALISTS

Manufacturers of Burner Quaris Precast

Combustion Chambers for Sectional Boilers ● Firebacks etc.

Official Stockists for G. R. Stein's Scottish Firebricks • Fireclays • Jointing Cements •

Castables • Mouldables etc.

REFRACTORIES IRELAND LTD.

Stonewall, BAILIEBOROUGH, Co. Cavan, Eire. Telephone 042-65123/65150.

their high pressure losses, excessive fan powers and noise levels. The generously dimensioned tubes reduce the tendency to fouling where heavy oil fuels are used.


The extended 'Maxecon' boiler range offers a wide choice of outputs at pressures up to 250 p.s.i.g., in addition, 'specials' for higher pressures are also available. Designed as a three pass fully wet back boiler for use with oil and gaseous fuels, its design criteria have proved in service over many years that it is one of the most efficient, reliable and accessible boilers produced. One of the features of the 'Maxecon' boiler is the ability. with twin furnace models, to operate for long periods on one furnace only. This gives high turn down ratios. If desired, an additional small panel gives the added facility of being carry out maintenance work on mechanical and electrical components of either burner and panel while the

other is in operation.

Further information from IES Industrial (Ireland) Ltd. in Northern and Southern Ireland.

Powrmatic

As a leader for some time in the industrial warm air heating business Powrmatic are set to take the plunge. The reason? The new Powrmatic Boiler. A range of 37 models designed for commercial and industrial applications with heat outputs from 60,000 to 700,000 Btu's. They'll supply them oil or gas fired with a burner that has been carefully selected to give optimum combustion efficiency. It probably won't come as any surprise to learn that these new boilers will be as well designed and constructed as everything else that comes from Powrmatic. Take the case for example. Two-colour selfinterlocking stove enamelled steel panels that are made to take the knocks. Inside, the boiler is constructed of highly corrosion-



One of Powrmatic's new oil- or gas-fired commercial/industrial boilers available from Heating Controls & Devices Ltd. There are 50 models in the range, with outputs from 60,000 to 2,000,000 Btu/h.

resistant cast iron sections to ensure a long and efficient life. And to make sure you lose no more precious heat than is necessary the unit is well insulated with mineral wool. Maximum advantage is taken of radiation from the combustion chamber too. The boiler is designed to give the maximum heat exchange.

Further information from Powrmatic or Heating Controls & Devices Ltd.

Robey

The new range of Incendo boilers is an addition to the existing comprehensive range of Lincoln boilers already marketed by Robey of Lincoln which are suitable for firing by the various types of fuel available. The Incendo boiler has been introduced into the Robey range in order to cater for an increasing market requirement for solid fuel


fired boilers and by its indroduction now enables Robey to offer its customers a wide choice of combustion equipment for soldifuel.

The Robey Incendo has been developed in conjunction with Greenforge Limited, and in the majority of cases, the boilers will be available as packaged units although some items of equipment may require re-fitting at site. These boilers are of the three pass wet back design and will be available for outputs from 5000 to 25,000 lbs. of steam/hour, from and at 100 degs. C.

Robey boilers are available from S L Combustions Ltd.



K. B. COMBUSTION LIMITED



The "Dunphy T" Series Heavy Oil Burner

SUPPLIERS AND INSTALLERS OF A COMPREHENSIVE RANGE OF OIL AND GAS FIRED BURNERS:-FROM 200,000 BTU/h to 30 MILLION BTU/u OR, 80 lb/hr STEAM TO 26,000 lb/hr *COMPLETE STEAM INSTALLATIONS*SALES AND SERVICE OF STEAM BOILERS:-FROM 1000 lbs/hr to 50,000 lbs/hr and up to 350 P.S.I.

FOR TECHNICAL SERVICE AND DATA CALL KEN BIRNEY AT -



K. B. COMBUSTION LIMITED

WHARTON HALL HAROLDS CROSS DUBLIN 6 TEL: 972168. (3 lines)



HEATING WHOLESALERS LTD

Thomastown, Co. Kilkenny, Tel: 056-24171 Telex 8797

Pressurised

R4

R5



Ratings: R4 524,000 Btuh to 1,280,000 Btuh R5 1,440,000 Btuh to 2,840,000 Btuh

Multifuel


Oil : Gas: Solid Fuel




Ratings:

M4 420,000 Btuh to 896,000 Btuh M5 780,000 Btuh to 1,480,000 Btuh






Solid Fuel



Gas



Natural Draught




P4

P5

Ratings: P4 560,000 Btuh to 1,328,000 Btuh P5 1,336,000 Btuh to 2,328,000 Btuh

Riello Burners




Press G Range
Outputs up to 12 million
Btu/h. Suitable for all leading
makes of Boilers.

Enquiries: Northern Area Mr C. Billings Tel: 01-517703 Southern Area Mr S. Doherty Tel: 056-24171



HEATING WHOLESALERS LTD





B & E Boilers Ltd

Easthampstead Road Bracknell, Berkshire England RG12 1NP

Tel.Bracknell (0344) 21341



A member of the Richardsons Westgarth Group